

2 – 4 Proven quality

- The tried and trusted stationary compact lift table
- 40 years of continuous development
- Tested in multiple shift operations
- Components are laser cut and robotically welded
- Scissors made of stiff rectangular tubing
- Special Swedish steel alloy



Lifting capacity at full load:
max. 10 cycles per hour in 2 shift operations (= max. 10000 cycles per year)


With double scissor mechanism

Model	2		3		4								
Max. load	kg	500	1000	1000	1000	1500	2000	2000	2000	2000	2000	2000	3000
Lifting range	mm	160 – 760	160 – 760	180 – 1000	180 – 1000	230 – 1330	200 – 1020	200 – 1020	220 – 1220	230 – 1530	250 – 1750	360 – 1960	250 – 1350
Platform length x width	mm	900 x 700	900 x 700	1300 x 800	1300 x 1000	1700 x 1000	1300 x 800	1300 x 1000	1500 x 1000	2000 x 900	2200 x 1200	1300 x 800	1700 x 900
Lifting time	sec	12	22	15	15	17	17	17	26	30	27	34	27
Power	kW	0.37	0.37	0.75	0.75	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Ref.		969 081-2G	969 082-2G	804 191-2G	760 557-2G	986 363-2G	969 083-2G	927 358-2G	986 362-2G	969 084-2G	986 366-2G	986 368-2G	986 365-2G
€		2.650,-	2.850,-	3.090,-	4.090,-	5.500,-	3.850,-	4.350,-	5.400,-	7.000,-	8.900,-	7.100,-	7.100,-




Foot operated control unit for:

1 – 4 Complete with up/down and emergency stop.




Safety bellows for:

2 – 4 Requires enlargement of platform.




Safety net for:

2 – 4 Requires enlargement of platform.




Safety curtain for:

2 – 4 Requires enlargement of platform.




Bridging plate for:

3 – 4 May require modification of tabletop.




Rotating platform for:

3 – 4 For 1000 – 2000 kg models. Results in reduced load capacity. Overall height + 61 mm.



Turntable for:

2 – 4 Raised turntable. Overall height + 55 – 61 mm.



Railing for:

2 – 4 Door with lateral hinge.

10021

YELLOW = 7 working days

FREE DELIVERY
SALES FAX: 1 800 677 301 (local rate)

KAISER + KRAFT
EVERYTHING FOR THE BUSINESS.