




Video
Online!

1–9 | Permanent lifting magnets

- Very user friendly by simply flipping the lever
- Highly concentrated energy guarantees constant and reliable grip
- Magnetic force ensures the load is handled gently and is never damaged



	1	2	3	4	5	6	7	8	9
Max. load permitted for flat material kg	125	150	250	300	300	500	600	1000	2000
Max. load permitted for round material kg	50	60	100	120	150	200	250	400	800
Weight kg	3.7	7.2	6	16.6	6.3	15	15.2	34	80
Width mm	79	79	79	106	79	106	106	133	166
Max. diameter for round material mm	300	240	300	290	300	400	400	450	600
Height mm	161	142	142	190	142	189	189	219	293
Length mm	121	189	189	250	189	249	249	342	441
Min. wall thickness for round material mm	10	6	10	8	10	15	15	25	35
Min. wall thickness for flat material mm	20	8	20	10	20	25	25	40	55
Max. workpiece length mm	1000	1500	1500	2000	1500	2000	2000	3000	3000
Ref.	927 475 6G	604 277 6G	927 471 6G	604 278 6G	609 989 6G	927 472 6G	609 990 6G	927 474 6G	927 476 6G
€	519.00	959.00	729.00	1425.00	939.00	1145.00	1545.00	1975.00	3450.00



Remote control
with 10 m cable
as standard.

10–13 | Electric wire rope winches

- Automatic shut down as soon as the rope is wound
- Immediately ready for use with rope and safety hooks
- Hooks rotate 360° with safety lock

Voltage: 230 V. Cable length: 5 m. Protection type: IP44.

	10	11	12	13
Max. load kg	80	160	230	300
Wire rope length m	23	30	24	24
Wire rope speed m/min	18 – 30	15 – 22	9 – 14	9 – 13
Power kW	0.8	1.2	1.3	1.5
Strength of current A	4	6	6.5	7.5
Weight kg	18	23	24	25
Ref.	604 998 6G	604 999 6G	601 994 6G	605 001 6G
€	959.00	1275.00	1695.00	1745.00

NEW


14–15 | PLX-III ratchet chain hoists

- Simple free-running mode
- Practical chain end piece
- Extremely robust

Lift: 1500 mm. Housing material: metal.

14 | Max. load: 750 kg. Number of chain strands: 1. Overall height (between device hook / load hook inner edges): 320 mm. Power required at full load: 14 daN.
Ref. 569 876 6G € 265.00

15 | Max. load: 1500 kg. Number of chain strands: 1. Overall height (between device hook / load hook inner edges): 380 mm. Power required at full load: 24 daN.
Ref. 569 877 6G € 309.00



16–17 | AH ratchet chain hoists

- Small lightweight design made of aluminium
- Can be used at ambient temperatures from –20 °C to +60 °C
- Robust chain end piece for reliable grip

Lift: 1.5 m. Number of chain strands: 1. Housing material: aluminium.

16 | Max. load: 250 kg. Overall height (between device hook / load hook inner edges): 223 mm. Power required at full load: 17.
Ref. 491 269 6G € 189.00

17 | Max. load: 800 kg. Overall height (between device hook / load hook inner edges): 329 mm. Power required at full load: 22.
Ref. 491 270 6G € 469.00