



VERIBOR
MADE IN GERMANY

18–24 | Suction lifters

- For lifting, carrying and holding glass, panes, etc.
- For level, non-porous surfaces
- Secure hold and convenient transport

Material: aluminium element.

		18	19	20	21	22	23	24
Head Ø	mm	120	120	120	120	120	120	210
Max. load	kg	30	35	60	60	70	100	120
Number of heads	pcs.	1	2	2	2	2	3	1
Material		aluminium element	plastic body	cast aluminium styrene butadiene rubber	aluminium element	aluminium element	aluminium element	aluminium element
Minimum order quantity								
1 pcs.	Ref.	759 405 6G	704 521 6G	455 688 6G	759 408 6G	759 412 6G	759 410 6G	759 417 6G
	€	69.90	94.90	125.00	59.90	74.90	89.90	349.00
								773 271 6G
								209.00
2 pcs.	Ref.	759 407 6G	704 522 6G		759 409 6G	759 413 6G	759 411 6G	
	€	62.90	89.90		52.90	69.90	84.90	

25–26 | PULLMASTER-II spur gear block and tackle units

- Tempered safety hook with custom-fit hook lock
- Robust, durable steel housing
- Flexible use due to hook suspension

Lift: 3 m. Housing material: sheet steel, powder coated.
Scope of delivery: with load chain.

25 | Max. load: 500 kg. Number of chain strands: 1. Overall height: 285 mm. Hand chain tensile force at full load: 26.2 daN.

Ref. 491 259 6G € 179.00

26 | Max. load: 1000 kg. Number of chain strands: 1. Overall height: 332 mm. Hand chain tensile force at full load: 32.4 daN.

Ref. 491 260 6G € 219.00



27–28 | Premium PRO spur gear block and tackle units

- Compact and lightweight
- Overload protection as standard (max. load 500 kg or higher)
- Annealed, galvanised load chain compliant with DIN EN 818-7-T

Lift: 3 m. Housing material: sheet steel, chrome plated.

27 | Max. load: 500 kg. Number of chain strands: 1. Overall height: 309 mm. Hand chain tensile force at full load: 24 daN.

Ref. 478 276 6G € 245.00

28 | Max. load: 1500 kg. Number of chain strands: 1. Overall height: 460 mm. Hand chain tensile force at full load: 36 daN.

Ref. 478 278 6G € 439.00



Value pack: pack of 2.

34–35 | Balancers

- Infinite max. load setting
- High gloss chrome plated steel housing
- Nylon cable with spring hook for attachment of tools

Cable length: 1700 mm. Weight: 0.4 kg.
Suspension eye: rigid. Design of hooks: safety hooks.
Material: steel, chrome plated. Weight per item: 0.2 kg. Pack of: 2.

34 | Max. load from – to: 0.5 – 1.5 kg.
Ref. 176 344 6G € /pack 48.90

35 | Max. load from – to: 1.5 – 3 kg.
Ref. 176 345 6G € /pack 49.90

29–33 | Professional balancers

- Comfortable working even with heavy tools due to weight counterbalance
- Durable and robust construction

		29	30	31	32	33
Max. load from – to	kg	1 – 2	2 – 3	2 – 4	4 – 6	6 – 8
Cable length	mm	1600	1600	2000	2000	2000
	Ref.	175 855 6G	175 856 6G	175 857 6G	175 858 6G	175 859 6G
	€	57.90	59.90	139.00	159.00	179.00

- Low friction stainless steel wire cable and adjustable load bearing range

Design of hooks: safety hooks. Housing material: aluminium.




29

36–41 | Balancers

- Comfortable working even with heavy tools due to weight counterbalance
- High quality construction made of cast aluminium housing and a stainless steel cable
- An integrated securing mechanism

prevents the load from dropping if the spring breaks (> 3 kg)

Cable length: 2000 mm.
Design of hooks: safety hooks.



		36	37	38	39	40	41
Max. load from – to	kg	4 – 7	7 – 10	10 – 14	14 – 18	18 – 22	22 – 25
	Ref.	175 868 6G	175 869 6G	175 871 6G	175 872 6G	175 873 6G	175 874 6G
	€	379.00	379.00	379.00	379.00	399.00	399.00

40

Free delivery when your order is over €200.

SALES PHONE 1800 677 300 (local rate)

KAISER+KRAFT