

# Carrier clamps

**Flexible, robust, versatile – the new carrier clamps from PFEIFER set the standard**



- Extremely easy to handle due to a slim housing
- Secured against unintentional opening under load
- Large gripping range for flexible use

The **KL model** makes lifting safe up to an angle of 120° – both when attaching loads from the side and lifting loads vertically, and when rotating metal sheets, steel panels, supports and structural steel elements by 180°.

The **M model** is ideally suited for structurally stable and non-rigid metal sheets held horizontally, while also allowing stacks of sheets and profiles to be lifted. The wide split lower jaw is outstandingly suited to gripping steel girders, regardless of whether from the side or the front.

**PFEIFER**

**NEW**



| Model | Gripping range | Max. load |      | 1 item     | 2+ items   | 4+ items   |
|-------|----------------|-----------|------|------------|------------|------------|
| 1     | 1 – 21 mm      | 600 kg    | Ref. | 499 090-2G | 499 097-2G | 499 098-2G |
|       |                |           | €    | 449,-      | 439,-      | 409,-      |
|       | 1 – 26 mm      | 1000 kg   | Ref. | 499 091-2G | 499 099-2G | 499 100-2G |
|       |                |           | €    | 519,-      | 499,-      | 449,-      |
|       | 1 – 35 mm      | 2000 kg   | Ref. | 499 092-2G | 499 101-2G | 499 102-2G |
|       |                |           | €    | 629,-      | 619,-      | 589,-      |
| 2     | 0 – 25 mm      | 500 kg    | Ref. | 499 093-2G | 499 103-2G | 499 104-2G |
|       |                |           | €    | 599,-      | 589,-      | 539,-      |
|       |                | 1000 kg   | Ref. | 499 094-2G | 499 105-2G | 499 106-2G |
|       |                |           | €    | 699,-      | 629,-      | 589,-      |
|       | 0 – 32 mm      | 2000 kg   | Ref. | 499 095-2G | 499 107-2G | 499 108-2G |
|       |                |           | €    | 1.145,-    | 1.045,-    | 969,-      |
|       | 0 – 38 mm      | 4000 kg   | Ref. | 499 096-2G | 499 109-2G | 499 110-2G |
|       |                |           | €    | 1.395,-    | 1.275,-    | 1.145,-    |

# HIT crane chains

**1, 2 or 4-leg crane chains**

- Made of special steel of quality class 10 (PAS 1061) for demanding lifting tasks
- Optimal protection of the chain links due to Pfeifer XLL coating
- Longer service life due to increased strength

**PFEIFER**

| Chain thickness                    | mm                | 6                     | 8          | 10         |            |          |
|------------------------------------|-------------------|-----------------------|------------|------------|------------|----------|
| Hook jaw width (with safety catch) | mm                | 19                    | 27         | 30         |            |          |
| Model                              | Effective length  |                       |            |            |            |          |
| 1 1-leg                            | 1000 mm           | Max. load             | kg         | 1400       | 2500       | 4000     |
|                                    |                   | Crane eye opening     | mm         | 110 x 60   | 110 x 60   | 135 x 75 |
|                                    |                   | Ref.                  | 512 377-2G | 512 380-2G | 512 384-2G |          |
|                                    |                   | €                     | 69,90      | 92,90      | 119,-      |          |
|                                    | 1500 mm           | Ref.                  | 512 378-2G | 512 381-2G | 512 385-2G |          |
|                                    |                   | €                     | 82,90      | 104,90     | 129,-      |          |
| 2000 mm                            | Ref.              | 512 379-2G            | 512 383-2G | 512 386-2G |            |          |
|                                    | €                 | 89,90                 | 115,-      | 149,-      |            |          |
| 2 2-leg                            | 1000 mm           | Max. load at 0 – 45°  | kg         | 2000       | 3500       | 5600     |
|                                    |                   | Max. load at 45 – 60° | kg         | 1400       | 2500       | 4000     |
|                                    | Crane eye opening | mm                    | 110 x 60   | 135 x 75   | 160 x 90   |          |
|                                    |                   | Ref.                  | 512 391-2G | 512 395-2G | 512 399-2G |          |
|                                    |                   | €                     | 129,-      | 165,-      | 239,-      |          |
|                                    | 1500 mm           | Ref.                  | 512 393-2G | 512 396-2G | 512 401-2G |          |
| €                                  |                   | 149,-                 | 189,-      | 265,-      |            |          |
| 2000 mm                            | Ref.              | 512 394-2G            | 512 398-2G | 512 402-2G |            |          |
|                                    | €                 | 165,-                 | 209,-      | 299,-      |            |          |
| 3 4-leg                            | 1000 mm           | Max. load at 0 – 45°  | kg         | 3000       | 5300       | 8000     |
|                                    |                   | Max. load at 45 – 60° | kg         | 2120       | 3750       | 6000     |
|                                    | Crane eye opening | mm                    | 135 x 75   | 160 x 90   | 180 x 100  |          |
|                                    |                   | Ref.                  | 512 406-2G | 512 409-2G | 512 412-2G |          |
|                                    |                   | €                     | 265,-      | 339,-      | 469,-      |          |
|                                    | 1500 mm           | Ref.                  | 512 407-2G | 512 410-2G | 512 413-2G |          |
| €                                  |                   | 295,-                 | 389,-      | 529,-      |            |          |
| 2000 mm                            | Ref.              | 512 408-2G            | 512 411-2G | 512 414-2G |            |          |
|                                    | €                 | 339,-                 | 429,-      | 569,-      |            |          |



Specified max. load applies to symmetrical loading on the legs. Max. inclination 60°.

**TRANSPORT**

YELLOW = 7 working days

**FREE DELIVERY**  
SALES FAX: 1 800 677 301 (local rate)

**KAISER + KRAFT**  
EVERYTHING FOR THE BUSINESS.