

## Thermoplastic elastomer tyres



### On polypropylene rims

- Low rolling resistance, smooth running
- Non-marking tyres, hardwearing
- Hardness 85 ±3 Shore A
- Temperature resistant from -10 °C to +70 °C

Zinc plated sheet steel housing, swivel bearings with double ball race.

### Plain bearings.

**proroll**



Non-marking

Particularly cost effective when purchased as a set.



## Polyurethane tyres



- On nylon rims
- Hardwearing and cut resistant
- Non-marking
- Hardness 95 Shore A
- Largely resistant against many thinned oils, greases, and alkaline solutions
- Temperature resistant from -15 °C to +60 °C

[www.kaiserkraft.ie](http://www.kaiserkraft.ie)  
**K1160**  
Please enter reference number for detailed information

**proroll**

Wheel Ø x width	mm	75 x 25	100 x 32	125 x 32
Max. load at 4 km/h	kg	75	80	100
Offset	mm	28	38	41
Overall height	mm	100	135	160
<b>With mounting plate</b>				
Screw hole diameter	mm	6	8.5	8.5
Plate dimensions	mm	60 x 60	77 x 67	77 x 67
Screw hole spacing	mm	48 / 38 x 48 / 38	61.5 / 51.5 x 56.5 / 46.5	61.5 / 51.5 x 56.5 / 46.5

Set offers					
<b>Set 1</b>	4 swivel castors, 2 with double stop	Ref.	969 286-2G	969 288-2G	969 291-2G
		€	23,90	45,90	54,90
<b>Set 2</b>	2 swivel castors with double stops, 2 fixed castors	Ref.	969 287-2G	969 289-2G	969 292-2G
		€	21,90	45,90	52,90

With bolt hole and screw fastening				
Screw hole diameter	mm	10.5	11	11
Threaded pin dimensions	mm	M 10 x 18	M 10 x 18	M 10 x 18

Set offers					
<b>Set 3</b>	4 swivel castors	Ref.	969 293-2G	969 295-2G	969 297-2G
		€	19,49	38,90	45,90
<b>Set 4</b>	4 swivel castors, 2 with double stop	Ref.	969 294-2G	969 296-2G	969 298-2G
		€	21,90	42,90	52,90

Housing and wheel axles made of rust free stainless steel. Swivel bearing with double ball race, swivel bearing protection.

### Plain bearings.



High load capacity



Non-marking



Rost frei

INOX STAINL 1.4301

Wheel Ø x width	mm	100 x 30	125 x 32	160 x 38
Max. load at 4 km/h	kg	140	180	240
Overall height	mm	128	155	197
Plate dimensions	mm	102 x 80	102 x 80	135 x 110
Screw hole spacing	mm	80 x 60	80 x 60	105 x 80
Screw hole diameter	mm	9	9	11
Hub length / bore	mm	40 / 12	44 / 15	58 / 20

<b>1</b>	swivel castor	Offset	mm	35	36	55
			Ref.	610 052-2G	610 057-2G	940 281-2G
			€	19,49	20,90	37,90
<b>2</b>	swivel castor with double stop	Offset	mm	35	36	55
			Ref.	610 053-2G	610 058-2G	940 282-2G
			€	24,90	26,90	45,90
<b>3</b>	fixed castor		Ref.	610 055-2G	610 059-2G	940 284-2G
			€	12,95	17,49	30,90
<b>Wheels</b>			Ref.	610 056-2G	610 060-2G	940 285-2G
			€	3,29	6,99	10,49



## Nylon wheels



- Maintenance free, smooth running
- Hardwearing
- Temperature resistant from -20 °C to +60 °C

Housing and wheel axles made of rust free stainless steel.

Swivel bearing with double ball race, swivel bearing protection.

### Plain bearings.



Maintenance-free



High load capacity



Rost frei

INOX STAINL 1.4301

Wheel Ø x width	mm	80 x 30	100 x 32	125 x 34	160 x 40	200 x 50
Max. load at 4 km/h	kg	150	150	180	300	300
Overall height	mm	108	128	155	197	235
Plate dimensions	mm	105 x 85	105 x 85	105 x 85	137 x 105	137 x 105
Screw hole spacing	mm	80 x 60	80 x 60	80 x 60	105 x 80	105 x 80
Screw hole diameter	mm	9	9	9	11	11
Hub length / bore	mm	40 / 12	40 / 12	48 / 10	58 / 20	60 / 20
<b>1</b>	swivel castor	Offset	mm	41	41	55
			Ref.	940 286-2G	940 290-2G	940 295-2G
			€	17,49	18,49	21,90
<b>2</b>	swivel castor with double stop	Offset	mm	41	41	55
			Ref.	940 287-2G	940 292-2G	940 296-2G
			€	24,90	24,90	28,90
<b>3</b>	fixed castor		Ref.	940 288-2G	940 293-2G	940 297-2G
			€	12,95	12,95	17,49
<b>Wheels</b>			Ref.	940 289-2G	940 294-2G	940 298-2G
			€	2,19	2,19	4,89



YELLOW = 7 working days

FREE DELIVERY  
SALES FAX: 1 800 677 301 (local rate)

**KAISER + KRAFT**  
EVERYTHING FOR THE BUSINESS.