



Nylon wheels



- Maintenance free, smooth running
- Hardwearing
- Largely resistant against many thinned acid and alkaline solutions
- Temperature resistant from -20 °C to +80 °C



Hard wearing



Maintenance-free

Sheet steel housing, zinc chromate finish. Swivel bearing with double ball race, swivel bearing protection.

Optionally with plain bearings or roller bearings.

Particularly cost effective when purchased as a set.



Wheel Ø x width	mm	65 x 30	80 x 35	100 x 38	125 x 38	150 x 40	200 x 50	80 x 35	100 x 38	125 x 38	
Max. load at 4 km/h	kg	100	150	180	200	300	300	150	180	200	
<b>Wheel bearing</b>		<b>plain bearing</b>						<b>roller bearing</b>			
Overall height	mm	93	100	128	155	185	235	100	128	155	
Screw hole spacing		75 x 45	76 - 80 x 60	76 - 80 x 60	76 - 80 x 60	105 x 75 - 80	105 x 75 - 80	76 - 80 x 60	76 - 80 x 60	76 - 80 x 60	
Screw hole diameter	mm	9	9	9	9	11	11	9	9	9	
Hub length / bore	mm	40 / 12	40 / 12	44 / 12	50 / 15	60 / 20	60 / 20	40 / 12	44 / 12	50 / 15	
<b>1 swivel castor</b>											
Offset		36	36	38	38	52	54	36	38	38	
Plate dimensions		100 x 70	105 x 80	105 x 80	105 x 80	135 x 110	135 x 110	105 x 80	105 x 80	105 x 80	
Ref.		192 910-2G	192 929-2G	192 945-2G	192 961-2G	192 996-2G	193 011-2G	892 122-2G	892 165-2G	892 211-2G	
€		8,19	9,19	9,19	11,95	19,49	25,90	10,49	10,49	14,49	
<b>2 swivel castor with double stop</b>											
Offset			36	38	38	52	54	36	38	38	
Plate dimensions			105 x 80	105 x 80	105 x 80	135 x 110	135 x 110	105 x 80	105 x 80	105 x 80	
Ref.			771 155-2G	771 171-2G	771 201-2G	771 236-2G	771 252-2G	892 130-2G	892 173-2G	892 238-2G	
€			14,49	12,95	20,90	54,90	39,90	16,49	19,49	20,90	
<b>3 fixed castor</b>											
Plate dimensions	mm	100 x 70	102 x 87	102 x 87	102 x 87	135 x 114	135 x 114	102 x 87	102 x 87	102 x 87	
Ref.		192 716-2G	192 724-2G	192 740-2G	192 767-2G	192 783-2G	192 821-2G	892 149-2G	892 181-2G	892 246-2G	
€		10,49	10,49	4,89	9,19	14,49	21,90	11,95	9,19	10,49	
<b>Wheels</b>											
Ref.		193 178-2G	193 186-2G	193 208-2G	193 224-2G	193 240-2G	193 267-2G	892 157-2G	892 203-2G	892 254-2G	
€		3,29	5,99	3,29	5,99	6,99	12,95	5,99	8,19	12,95	
<b>Set offers</b>											
<b>Set 1</b>		2 swivel castors, 2 swivel castors with double stops									
Ref.			986 094-2G	986 099-2G	986 104-2G				986 096-2G	986 102-2G	986 106-2G
€			42,90	42,90	47,90				45,90	89,90	47,90
<b>Set 2</b>		2 swivel castors with double stops, 2 fixed castors									
Ref.			986 095-2G	986 101-2G	986 105-2G				986 098-2G	986 103-2G	986 107-2G
€			64,90	69,90	42,90				42,90	77,90	45,90



Nylon wheels



- Extremely hardwearing
- Largely resistant against many thinned acid and alkaline solutions
- Temperature resistant from -40 °C to +80 °C



Hard wearing

Thermoplastic nylon based plastic.

Optionally with plain bearings or deep groove ball bearings.

Wheel Ø x width	mm	50 x 25	65 x 30	70 x 30	75 x 23	80 x 35	100 x 40	125 x 40	150 x 50	200 x 50	250 x 50
Max. load at 4 km/h	kg	150	170	200	200	300	450	600	600	1000	1000
Hub length	mm	30	35	40	25	35	50	53	55	52	58
<b>plain bearing</b>	Hub bore	mm	10	10	10	15	20	15	20	20	25
	Ref.	194 832-2G	194 840-2G	194 859-2G	194 867-2G	194 875-2G	194 697-2G	194 700-2G	194 719-2G	194 743-2G	194 778-2G
	€	3,29	4,89	5,99	5,99	11,95	17,49	21,90	23,90	34,90	54,90
<b>deep groove ball bearing</b>	Hub bore	mm				12	12	20	20	20	
	Ref.					194 689-2G	194 549-2G	194 557-2G	194 565-2G	194 603-2G	
	€					29,90	31,90	47,90	49,90	62,90	

BLUE = 14 working days