

Two component solid rubber tyres

On sheet steel rims

- Very smooth running
- Non-marking
- Hardness 65 Shore A
- Temperature resistant from -25 °C to +80 °C

Housing and wheel rims made of sheet steel, electrolytically zinc plated and blue passivated. Swivel bearing with double-ball race, smooth rolling with a minimum of play.

Tyres made of two-component solid rubber with hard tyre bed and highly elastic running surface, black. In comparison to solid rubber, increased load capacity and smoother run with less rolling resistance.

Roller bearings.



Low rolling resistance



High load capacity



TRANSPORT

Wheel Ø x width	mm	125 x 37.5	140 x 37.5	160 x 40	180 x 50	200 x 50	250 x 60	
Max. load at 4 km/h	kg	120	175	225	300	350	450	
Overall height	mm	150	170	195	215	235	295	
Plate dimensions	mm	100 x 85	140 x 110	140 x 110	140 x 110	140 x 110	175 x 175	
Screw hole spacing	mm	80 x 60	105 x 75 - 80	105 x 75 - 80	105 x 75 - 80	105 x 75 - 80	140 x 140	
Screw hole diameter	mm	9	11	11	11	11	15	
Hub length / bore	mm	45 / 15	45 / 15	60 / 20	60 / 20	60 / 20	65 / 25	
1 swivel castor	Offset	mm	40	50	60	60	65	70
		Ref.	179 229-2G	179 240-2G	179 230-2G	191 507-2G	179 231-2G	179 232-2G
2 swivel castor with double stop	Offset	mm	40	50	60	60	65	70
		Ref.	179 228-2G	179 242-2G	179 239-2G	751 804-2G	179 238-2G	179 237-2G
3 fixed castor	Offset	mm	40	50	60	60	65	70
		Ref.	179 233-2G	179 241-2G	179 234-2G	190 624-2G	179 235-2G	179 236-2G
Wheels	Ref.	€	18,49	30,90	37,90	39,90	52,90	104,90
		€	179 223-2G	179 224-2G	179 225-2G	191 639-2G	179 226-2G	179 227-2G
		€	12,95	14,49	14,49	31,90	42,90	82,90

Solid rubber tyres

On plastic rims

- For light to medium duty requirements
- Hardness 85 ±3 Shore A
- Temperature resistant from -5 °C to +60 °C

Sheet steel housing, zinc plated and blue passivated. Swivel bearing with double ball race and swivel bearing protection. **Roller bearings.**



www.kaiserkraft.ie

K1160

Please enter reference number for detailed information



Model with bolt hole
ONLINE!

Wheel Ø x width	mm	80 x 25	100 x 30	125 x 38	160 x 40	200 x 50	
Max. load at 4 km/h	kg	50	70	100	135	205	
Overall height	mm	100	125	155	200	240	
Screw hole spacing	mm	76 - 80 x 60	76 - 80 x 60	76 - 80 x 60	75 - 80 x 105	75 - 80 x 105	
Screw hole diameter	mm	9	9	9	11	11	
Hub length / bore	mm	40 / 12	40 / 12	50 / 15	58 / 20	58 / 20	
1 swivel castor	Offset	mm	36	38	38	55	55
		Plate dimensions	mm	105 x 80	105 x 80	105 x 80	137 x 105
2 swivel castor with double stop	Offset	mm	36	38	38	55	55
		Plate dimensions	mm	105 x 80	105 x 80	105 x 80	137 x 105
3 fixed castor	Plate dimensions	mm	102 x 87	102 x 87	102 x 87	137 x 115	137 x 115
		Ref.	969 250-2G	969 254-2G	969 259-2G	969 279-2G	969 284-2G
Wheels	Ref.	€	4,89	6,99	8,19	11,95	18,49
		€	969 251-2G	969 255-2G	969 260-2G	969 280-2G	969 285-2G
		€	3,29	3,29	4,89	4,89	8,19

YELLOW =
7 working days

FREE DELIVERY
SALES FAX: 1 800 677 301 (local rate)

KAISER + KRAFT
EVERYTHING FOR THE BUSINESS.