

## Pneumatic tyres

### On sheet steel rims

- Very good shock absorption
- Low rolling resistance on rough flooring
- Easy on floors due to air cushioning



Low rolling resistance

## Swivel castors and fixed castors

### 1 – 5 Up to wheel Ø 260 mm

Sheet steel housing, bright zinc plated, with dual ball bearings in live ring, splash water protection. On swivel castors, central bolts are secured with nut and lock washer.

## Wheels

### 1 – 5 Wheel Ø 200 – 260 mm

With 1-part, powder coated sheet steel rim.

### 7 – 10 Wheel Ø 400 mm

With 1-part, black powder coated, welded sheet steel deep bed rim.

Wheels with welded steel hubs.

### Note on air pressure:

If the pressure is reduced by 0.5 bar the max. load is reduced by approx. 15%, at 1.0 bar by approx. 30%.

For optimum rolling characteristics, the recommended air pressure must be maintained.

We recommend checking the air pressure on a regular basis.

Puncture proof model

**ONLINE!**

## Accessories

### Dust caps

Pack of 4.

For hub bore	mm	20	25
Ref.		985 939-2G	985 940-2G
€/ pack		4,89	4,89

### On request

- Wheel sets with pneumatic tyres
- Spoke wheels

Additional hub bores, nylon plain bearings, various wheel sizes with plastic rims and other tyres are available upon request.



Wheel set (similar)



Spoke wheels

Model		1	2	3	4	5	6
Wheel Ø x width	mm	200 x 50	210 x 65	260 x 85	260 x 85	260 x 85	260 x 85
Max. load at 4 km/h	kg	75	100	200	200	200	200
Wheel bearing		roller bearing				precision ball bearing	
Tyre profile		grooved profile	grooved profile	grooved profile	block profile	grooved profile	block profile
Tyre pressure	bar	2.5	2.5	2.5	2.5	2.5	2.5
Overall height	mm	230	245	295	295	295	295
Screw hole diameter	mm	11	11	15	15	15	15
Hub length / bore	mm	60 / 20	75 / 20	75 / 20	75 / 20	75 / 20	75 / 20
swivel castor	Offset	mm	54	62	70	70	70
	Plate dimensions	mm	135 x 110	135 x 110	175 x 175	175 x 175	175 x 175
	Screw hole spacing	mm	105 x 80	105 x 80	140 x 140	140 x 140	140 x 140
	Ref.	196 983-2G	196 991-2G	197 009-2G	197 289-2G	196 975-2G	197 254-2G
	€	29,90	39,90	59,90	59,90	67,90	67,90
fixed castor	Plate dimensions	mm	135 x 105	135 x 105	220 x 125	220 x 125	220 x 125
	Screw hole spacing	mm	105 x 80	105 x 80	190 x 75	190 x 75	190 x 75
	Ref.	196 940-2G	196 959-2G	196 967-2G	197 203-2G	196 932-2G	197 165-2G
	€	24,90	31,90	49,90	46,90	57,90	59,90
Wheels	Ref.	197 033-2G	197 068-2G	197 084-2G	197 416-2G	197 017-2G	197 327-2G
	€	17,95	26,90	19,95	18,95	30,90	30,90

Model		7	8	9	10
Wheel Ø x width	mm	400 x 100	400 x 100	400 x 100	400 x 100
Max. load at 4 km/h	kg	300	300	300	300
Wheel bearing		roller bearing		precision ball bearing	
Tyre profile		grooved profile		block profile	block profile
Tyre pressure	bar	2.5		2.5	2.5
Hub length / bore	mm	88 / 25		88 / 25	88 / 25
Wheels	Ref.	197 483-2G	944 410-2G	944 409-2G	944 411-2G
	€	23,90	25,90	26,90	52,90

YELLOW =  
7 working days

**FREE DELIVERY**  
**SALES FAX: 1 800 677 301 (local rate)**

**KAISER + KRAFT**  
EVERYTHING FOR THE BUSINESS.