




**proroll**

**Polyurethane tyres**




- On aluminium rims
- Extremely durable for high performance
- Low rolling resistance
- Hardness 92 ±3 Shore A
- Temperature resistant from -5 °C to +80 °C

Reinforced housing made of zinc plated sheet steel. Swivel bearing without central bolt with hardened, double ball race, swivel bearing protection. **Ball bearings.**



Swivel bearing



Low rolling resistance Non-marking High load capacity

Wheel Ø x width	mm	100 x 40	125 x 40	160 x 50	200 x 50
Max. load at 4 km/h	kg	280	350	500	700
Overall height	mm	130	178	215	245
Screw hole spacing	mm	80 x 60	105 x 80	105 x 80	105 x 80
Screw hole diameter	mm	9	11	11	11
Hub length / bore	mm	41 / 12	50 / 20	60 / 20	60 / 20
<b>1</b> swivel castor					
	Offset	mm	40	50	53
	Plate dimensions	mm	105 x 80	135 x 110	135 x 110
	Ref.	969 306-2G	969 310-2G	969 315-2G	969 319-2G
	€	31,90	54,90	67,90	72,90
<b>2</b> swivel castor with double stop					
	Offset	mm	40	50	53
	Plate dimensions	mm	105 x 80	135 x 110	135 x 110
	Ref.	969 307-2G	969 312-2G	969 316-2G	969 321-2G
	€	38,90	59,90	72,90	82,90
<b>3</b> fixed castor					
	Plate dimensions	mm	105 x 85	135 x 114	135 x 114
	Ref.	969 308-2G	969 313-2G	969 317-2G	969 322-2G
	€	26,90	38,90	52,90	59,90
<b>Wheels</b>					
	Ref.	969 309-2G	969 314-2G	969 318-2G	969 323-2G
	€	18,49	26,90	37,90	42,90



[www.kaiserkraft.ie](http://www.kaiserkraft.ie)  
**K1160**  
Please enter reference number for detailed information




**Nylon wheels**




- Hardwearing
- Largely resistant to thinned acids and alkaline solutions
- Temperature resistant from -20 °C to +80 °C

Steel housing, welded, with zinc chromate finish. Swivel bearings with double ball race. Live ring with labyrinth seal. With lubrication nipple, centre bolts screwed on and secured.

**Ball bearings.**



Swivel fork head



Hard wearing High load capacity

Wheel Ø x width	mm	125 x 50	150 x 50	200 x 50
Max. load at 4 km/h	kg	840	960	1200
Overall height	mm	170	200	245
Plate dimensions	mm	135 x 110	135 x 110	135 x 110
Screw hole spacing	mm	105 x 75 - 80	105 x 75 - 80	105 x 75 - 80
Screw hole diameter	mm	11	11	11
Hub length	mm	60	60	60
Hub bore	mm	20	20	20
<b>1</b> swivel castor				
	Offset	mm	48	58
	Ref.	940 323-2G	940 327-2G	940 332-2G
	€	72,90	84,90	89,90
<b>2</b> swivel castor with double stop				
	Offset	mm	48	58
	Ref.	944 412-2G	944 413-2G	944 414-2G
	€	92,90	97,90	109,-
<b>3</b> fixed castor				
	Ref.	940 325-2G	940 329-2G	940 334-2G
	€	42,90	52,90	54,90
<b>Wheels</b>				
	Ref.	940 326-2G	940 331-2G	940 335-2G
	€	23,90	28,90	34,90

BLUE = 14 working days