



With plastic rollers and flexible centre section

Downward movement without drive: with 2 to 5 % pitch

Inner curve radius of at least 450 mm

Flexible conveyors

- Optimise material flow in the workshop and suitable for mobile use
- Space saving storage when collapsed
- Durable, bright zinc plated model


The GURA flexible roller conveyors can be used in all areas of load transport in the workshop. Especially when a permanently installed system is not welcome, then this mobile version can be used.

They allow your own logistics structures to be optimally modified and extended to suit requirements. The tracks are individual length and height adjustable, while curves of up to 180° can be formed at the same time.

Other features:

- Upper track edge is height adjustable from 720 – 1150 mm.
- For transporting goods 440 – 700 mm.
- Axle spacing 150 mm when track is fully extended.
- Castors (Ø 50 mm) ball bearing mounted on 8 mm axles.


Other dimensions and electric drive available on request.



Flexible roller conveyors

- Rollers made of impact resistant plastic
- Only for transporting goods with a level base as well as with raised edges, profiles and lengthways rails
- Additional flexible centre section for track widths from 600 mm

2 rollers (Ø 50 mm) on 8 mm axle.



Flexible skate wheel conveyors

- Optionally available made of steel or impact resistant plastic
- For transporting goods with a level base surface
- Additional flexible centre section for track widths from 500 mm

Skate wheels (Ø 48 mm) with ball bearings on 8 mm axle, with spacing sleeves in between.

Type	Track width	Width of goods conveyed	Ref.	€
Track length 1300 – 4500 mm, 3 support feet, max. load 100 kg	400 mm	250 – 600 mm	714 004-2G	1.195,-
	500 mm	250 – 800 mm	714 006-2G	1.395,-
	600 mm	250 – 900 mm	859 435-2G	1.575,-
Track length 1700 – 6300 mm, 3 support feet, max. load 100 kg	400 mm	250 – 600 mm	714 010-2G	1.625,-
	500 mm	250 – 800 mm	714 013-2G	1.895,-
	600 mm	250 – 900 mm	859 451-2G	2.090,-
Track length 2200 – 8000 mm, 5 support feet, max. load 125 kg	400 mm	250 – 600 mm	714 017-2G	2.050,-
	500 mm	250 – 800 mm	714 019-2G	2.450,-
	600 mm	250 – 900 mm	859 486-2G	2.690,-
Track length 2600 – 9800 mm, 6 support feet, max. load 125 kg	400 mm	250 – 600 mm	968 788-2G	2.450,-
	500 mm	250 – 800 mm	714 026-2G	2.890,-
	600 mm	250 – 900 mm	859 508-2G	3.550,-

The specified max. load applies to the flexible roller conveyor between two supports

Type	Track width	Width of goods conveyed	Skate wheels per axle	steel		€
				Ref.	Ref.	
Track length 1300 – 4500 mm, 3 support feet, max. load 100 kg	400 mm	200 – 600 mm	4	714 029-2G	714 030-2G	919,-
	500 mm	200 – 800 mm	5	859 729-2G	859 737-2G	1.195,-
	600 mm	200 – 900 mm	6	859 826-2G	859 834-2G	1.275,-
Track length 1700 – 6300 mm, 4 support feet, max. load 100 kg	400 mm	200 – 600 mm	4	714 033-2G	714 034-2G	1.325,-
	500 mm	200 – 800 mm	5	859 745-2G	859 753-2G	1.625,-
	600 mm	200 – 900 mm	6	859 842-2G	859 966-2G	1.725,-
Track length 2200 – 8000 mm, 5 support feet, max. load 125 kg	400 mm	200 – 600 mm	4	714 037-2G	714 039-2G	1.725,-
	500 mm	200 – 800 mm	5	859 761-2G	859 788-2G	2.050,-
	600 mm	200 – 900 mm	6	859 850-2G	859 869-2G	2.190,-
Track length 2600 – 9800 mm, 6 support feet, max. load 125 kg	400 mm	200 – 600 mm	4	714 042-2G	714 043-2G	2.050,-
	500 mm	200 – 800 mm	5	859 796-2G	859 818-2G	2.490,-
	600 mm	200 – 900 mm	6	859 877-2G	859 885-2G	2.650,-

The specified max. load applies to the flexible skate wheel conveyor between two supports



Fixed end stop



Folding end stop

End stops

Suitable for all flexible conveyor models.

Type of end stop	fixed		folding	
	Ref.	€	Ref.	€
Track width 400 mm	859 575-2G	54,90	859 605-2G	74,90
Track width 500 mm	859 583-2G	57,90	859 613-2G	74,90
Track width 600 mm	859 591-2G	59,90	859 621-2G	79,90



For roller conveyors



For skate wheel conveyors

Connector sections

To connect several tracks together.

Length 330 mm.

Type	For roller conveyor plastic		For skate wheel conveyor steel		€
	Ref.	€	Ref.	Ref.	
Track width 400 mm	859 524-2G	97,90	859 893-2G	859 907-2G	97,90
Track width 500 mm	859 540-2G	109,-	859 915-2G	859 923-2G	109,-
Track width 600 mm	859 567-2G	125,-	859 931-2G	859 958-2G	125,-

BLUE =
14 working days