



Special designs, 45° curves and passages available on request.



## 19–24 | Skate wheel conveyors

- Optimise the material flow in the company
- Modular system, making it individually adjustable
- A very low empty weight makes it suitable for flexible use

Design of frame: steel, zinc plated. Skate wheel material: steel, zinc plated. Max. load: 200 kg. Overall height: 69 mm.

|                          |      | 19         | 20         | 21         | 22         | 23         | 24         |
|--------------------------|------|------------|------------|------------|------------|------------|------------|
| Track width              | mm   | 300        | 300        | 300        | 500        | 500        | 500        |
| Axle spacing             | mm   | 50         | 75         | 100        | 50         | 75         | 100        |
| Width of goods conveyed  | mm   | 150 – 400  | 150 – 400  | 150 – 400  | 150 – 600  | 150 – 600  | 150 – 600  |
| Length of goods conveyed | mm   | 150 – 1000 | 225 – 1000 | 300 – 1000 | 150 – 1000 | 225 – 1000 | 300 – 1000 |
| Skate wheel arrangement  |      | 3 : 3      | 3 : 3      | 3 : 3      | 5 : 5      | 5 : 5      | 5 : 5      |
| Overall width            | mm   | 340        | 340        | 340        | 540        | 540        | 540        |
| <b>Type</b>              |      |            |            |            |            |            |            |
| straight 1 m             | Ref. | 759 579 6G | 759 574 6G | 759 545 6G | 759 594 6G | 759 590 6G | 759 584 6G |
|                          | €    | 215.00     | 179.00     | 159.00     | 309.00     | 239.00     | 209.00     |
| straight 1.5 m           | Ref. | 759 580 6G | 759 576 6G | 759 547 6G | 759 595 6G | 759 591 6G | 759 585 6G |
|                          | €    | 309.00     | 249.00     | 199.00     | 419.00     | 329.00     | 295.00     |
| straight 2 m             | Ref. | 759 581 6G | 759 577 6G | 759 559 6G | 759 596 6G | 759 592 6G | 759 586 6G |
|                          | €    | 389.00     | 299.00     | 275.00     | 519.00     | 399.00     | 359.00     |

## 25–30 | Light duty skate wheel conveyors, steel frame with plastic skate wheels

- Optimises the material flow in the company
- Modular system, making it individually adjustable
- A very low empty weight makes it suitable for flexible use

Design of frame: steel, zinc plated. Skate wheel material: plastic. Max. load: 200 kg. Overall height: 69 mm.

|                          |      | 25         | 26         | 27         | 28         | 29         | 30         |
|--------------------------|------|------------|------------|------------|------------|------------|------------|
| Track width              | mm   | 300        | 300        | 300        | 500        | 500        | 500        |
| Axle spacing             | mm   | 50         | 75         | 100        | 50         | 75         | 100        |
| Width of goods conveyed  | mm   | 150 – 400  | 150 – 400  | 150 – 400  | 150 – 600  | 150 – 600  | 150 – 600  |
| Length of goods conveyed | mm   | 150 – 1000 | 225 – 1000 | 300 – 1000 | 150 – 1000 | 225 – 1000 | 300 – 1000 |
| Skate wheel arrangement  |      | 3 : 3      | 3 : 3      | 3 : 3      | 5 : 5      | 5 : 5      | 5 : 5      |
| Overall width            | mm   | 340        | 340        | 340        | 540        | 540        | 540        |
| <b>Type</b>              |      |            |            |            |            |            |            |
| straight 1 m             | Ref. | 903 480 6G | 903 474 6G | 903 491 6G | 903 506 6G | 903 501 6G | 903 496 6G |
|                          | €    | 229.00     | 179.00     | 159.00     | 309.00     | 239.00     | 199.00     |
| straight 1.5 m           | Ref. | 903 481 6G | 903 475 6G | 903 492 6G | 903 508 6G | 903 502 6G | 903 497 6G |
|                          | €    | 309.00     | 259.00     | 209.00     | 409.00     | 329.00     | 295.00     |
| straight 2 m             | Ref. | 903 482 6G | 903 476 6G | 903 494 6G | 903 509 6G | 903 503 6G | 903 498 6G |
|                          | €    | 389.00     | 309.00     | 275.00     | 519.00     | 399.00     | 359.00     |

## 31–34 | ° curves

- Modular system facilitates rapid material flow
- High quality workmanship
- Ideal supplement in a conveyor system

Overall height: 69 mm. Curve: 90°. Radius of curve: 800 mm. Roller Ø: 48 mm. Design of frame: steel, zinc plated. Max. load with 1 m frame support spacing: 200 kg.

|                             |      | 31         | 32         | 33         | 34         |
|-----------------------------|------|------------|------------|------------|------------|
| Track width                 | mm   | 300        | 300        | 500        | 500        |
| Axle spacing                | mm   | 75         | 100        | 75         | 100        |
| Overall width               | mm   | 340        | 340        | 540        | 540        |
| Length of goods conveyed    | mm   | 225 – 1000 | 300 – 1000 | 225 – 1000 | 300 – 1000 |
| Skate wheel arrangement     |      | 3 : 3      | 3 : 3      | 5 : 5      | 5 : 5      |
| Width of goods conveyed     | mm   | 150 – 400  | 150 – 400  | 150 – 600  | 150 – 600  |
| <b>Skate wheel material</b> |      |            |            |            |            |
| plastic                     | Ref. | 903 479 6G | 903 473 6G | 903 505 6G | 903 500 6G |
|                             | €    | 329.00     | 289.00     | 429.00     | 359.00     |
| steel, zinc plated          | Ref. | 759 583 6G | 759 573 6G | 759 599 6G | 759 588 6G |
|                             | €    | 329.00     | 275.00     | 429.00     | 359.00     |

Free delivery when your order is over €200.

SALES PHONE 1800 677 300 (local rate)

KAISER+KRAFT