

19



## 19–27 | Light duty roller conveyors, aluminium frame with plastic rollers

- Optimises the material flow in the company
- Modular system, making it individually adjustable
- A very low empty weight makes it suitable for flexible use

Design of frame: aluminium. Overall height: 70 mm. Roller Ø: 50 mm. Roller material: plastic. Max. load with 1 m frame support spacing: 200 kg.

Delivery does not include double stands or side guide rails. Suitable additions can be found under Accessories / spare parts, or in the Combinations field.

Alternative versions, 45° curves and passages available on request.

|                         |      | 19         | 20         | 21         | 22         | 23         | 24         | 25         | 26         | 27         |
|-------------------------|------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| Track width             | mm   | 300        | 300        | 300        | 500        | 500        | 500        | 600        | 600        | 600        |
| Overall width           | mm   | 340        | 340        | 340        | 540        | 540        | 540        | 640        | 640        | 640        |
| Axle spacing            | mm   | 62.5       | 75         | 100        | 62.5       | 75         | 100        | 62.5       | 75         | 100        |
| Width of goods conveyed | mm   | 450        | 450        | 450        | 600        | 600        | 600        | 750        | 750        | 750        |
| Installation length     | mm   | 300        | 300        | 300        | 502        | 502        | 502        | 603        | 603        | 603        |
| Tube length             | mm   | 283        | 283        | 283        | 485        | 485        | 485        | 586        | 586        | 586        |
| Type                    |      |            |            |            |            |            |            |            |            |            |
| 90° curve               | Ref. |            | 903 644 6G | 903 857 6G |            | 903 654 6G | 903 858 6G |            | 903 665 6G | 903 859 6G |
|                         | €    |            | 389.00     | 369.00     |            | 639.00     | 529.00     |            | 699.00     | 549.00     |
| straight 1 m            | Ref. | 903 860 6G | 903 640 6G | 903 635 6G | 903 864 6G | 903 650 6G | 903 645 6G | 903 869 6G | 903 660 6G | 903 656 6G |
|                         | €    | 219.00     | 189.00     | 159.00     | 265.00     | 219.00     | 179.00     | 275.00     | 229.00     | 189.00     |
| straight 1.5 m          | Ref. | 903 861 6G | 903 641 6G | 903 636 6G | 903 865 6G | 903 651 6G | 903 646 6G | 903 870 6G | 903 661 6G | 903 657 6G |
|                         | €    | 309.00     | 275.00     | 215.00     | 339.00     | 299.00     | 265.00     | 369.00     | 329.00     | 275.00     |
| straight 2 m            | Ref. | 903 862 6G | 903 642 6G | 903 637 6G | 903 866 6G | 903 652 6G | 903 648 6G | 903 871 6G | 903 662 6G | 903 658 6G |
|                         | €    | 379.00     | 339.00     | 289.00     | 429.00     | 379.00     | 319.00     | 459.00     | 399.00     | 339.00     |

28



## 28–36 | Light duty roller conveyors, steel frame with plastic rollers

- Optimises the material flow in the company
- Modular system, making it individually adjustable
- A very low empty weight makes it suitable for flexible use

Design of frame: steel, zinc plated. Overall height: 70 mm. Roller Ø: 50 mm. Roller material: plastic. Max. load with 1 m frame support spacing: 200 kg.

|                         |      | 28         | 29         | 30         | 31         | 32         | 33         | 34         | 35         | 36         |
|-------------------------|------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| Track width             | mm   | 300        | 300        | 300        | 500        | 500        | 500        | 600        | 600        | 600        |
| Overall width           | mm   | 340        | 340        | 340        | 540        | 540        | 540        | 640        | 640        | 640        |
| Axle spacing            | mm   | 62.5       | 75         | 100        | 62.5       | 75         | 100        | 62.5       | 75         | 100        |
| Width of goods conveyed | mm   | 450        | 450        | 450        | 600        | 600        | 600        | 750        | 750        | 750        |
| Installation length     | mm   | 300        | 300        | 300        | 502        | 502        | 502        | 603        | 603        | 603        |
| Tube length             | mm   | 283        | 283        | 283        | 485        | 485        | 485        | 586        | 586        | 586        |
| Type                    |      |            |            |            |            |            |            |            |            |            |
| 90° curve               | Ref. |            | 903 614 6G | 903 840 6G |            | 903 624 6G | 903 842 6G |            | 903 634 6G | 903 843 6G |
|                         | €    |            | 389.00     | 379.00     |            | 639.00     | 529.00     |            | 699.00     | 549.00     |
| straight 1 m            | Ref. | 903 844 6G | 903 609 6G | 903 605 6G | 903 848 6G | 903 619 6G | 903 615 6G | 903 853 6G | 903 629 6G | 903 625 6G |
|                         | €    | 219.00     | 185.00     | 159.00     | 265.00     | 215.00     | 179.00     | 275.00     | 219.00     | 195.00     |
| straight 1.5 m          | Ref. | 903 845 6G | 903 610 6G | 903 606 6G | 903 849 6G | 903 621 6G | 903 616 6G | 903 854 6G | 903 631 6G | 903 626 6G |
|                         | €    | 299.00     | 275.00     | 219.00     | 339.00     | 309.00     | 265.00     | 369.00     | 329.00     | 275.00     |
| straight 2 m            | Ref. | 903 846 6G | 903 611 6G | 903 607 6G | 903 851 6G | 903 622 6G | 903 617 6G | 903 855 6G | 903 632 6G | 903 627 6G |
|                         | €    | 379.00     | 329.00     | 295.00     | 429.00     | 379.00     | 319.00     | 459.00     | 389.00     | 339.00     |

### 37–41 | Dual frame supports

Material: rectangular steel pipe, galvanised. Max. load: 200 kg.

39



Max. load 200 kg.

40



|                         |      | 37         | 38         | 39         | 40         | 41         |
|-------------------------|------|------------|------------|------------|------------|------------|
| Track width             | mm   | 200        | 300        | 400        | 500        | 600        |
| Height adjustment range |      |            |            |            |            |            |
| 330 – 480 mm            | Ref. | 977 617 6G | 903 676 6G | 977 622 6G | 903 677 6G | 903 878 6G |
|                         | €    | 92.90      | 84.90      | 92.90      | 84.90      | 84.90      |
| 380 – 580 mm            | Ref. | 977 618 6G | 903 678 6G | 977 623 6G | 903 679 6G | 903 879 6G |
|                         | €    | 94.90      | 84.90      | 94.90      | 89.90      | 89.90      |
| 470 – 750 mm            | Ref. | 977 619 6G | 903 681 6G | 977 625 6G | 903 682 6G | 903 880 6G |
|                         | €    | 99.90      | 94.90      | 99.90      | 94.90      | 94.90      |
| 580 – 950 mm            | Ref. | 977 620 6G | 903 683 6G | 977 626 6G | 903 684 6G | 903 881 6G |
|                         | €    | 99.90      | 94.90      | 99.90      | 94.90      | 94.90      |
| 730 – 1250 mm           | Ref. | 977 621 6G | 903 685 6G | 977 627 6G | 903 686 6G | 903 882 6G |
|                         | €    | 104.90     | 97.90      | 109.00     | 97.90      | 99.90      |

### 42–44 | Lightweight tripod frame supports, zinc plated

Material: zinc plated. Max. load: 100 kg.



Max. load 100 kg.

|                         |      | 42         | 43         | 44         |
|-------------------------|------|------------|------------|------------|
| Track width             | mm   | 300        | 500        | 600        |
| Height adjustment range |      |            |            |            |
| 210 – 350 mm            | Ref. | 903 667 6G | 903 668 6G | 903 873 6G |
|                         | €    | 64.90      | 64.90      | 72.90      |
| 340 – 590 mm            | Ref. | 903 669 6G | 903 670 6G | 903 874 6G |
|                         | €    | 69.90      | 69.90      | 69.90      |
| 430 – 720 mm            | Ref. | 903 672 6G | 903 673 6G | 903 875 6G |
|                         | €    | 69.90      | 69.90      | 72.90      |
| 590 – 1080 mm           | Ref. | 903 674 6G | 903 675 6G | 903 877 6G |
|                         | €    | 72.90      | 72.90      | 72.90      |

Free delivery when your order is over €200.

SALES PHONE 1800 677 300 (local rate)

KAISER+KRAFT

177