



Please ask for details.



**Video
Online!**

- Very narrow width optimal for narrow passageways
- With roll-off mechanism
- Optimised load centre

Type: without wheel set. Fork pocket dimensions: 200 x 80 mm. Material: sheet steel. Material thickness: 3 mm.

			1	2	3	4	5	6
Capacity	m³		0.3	0.5	0.75	1	1.5	2
Max. load	kg		1500	2500	3000	3000	3000	3000
Overall length	mm		1160	1550	1760	1760	1760	1810
Overall width	mm		820	820	820	1060	1560	1560
Overall height	mm		825	1045	1270	1270	1270	1480
Height of front edge	mm		726	951	1080	1080	1080	1083
Forklift pocket spacing	mm		225	225	225	410	600	600
Finish	Colour							
hot dip galvanised	hot dip galvanised	Ref.	908 881 6G	908 887 6G	910 225 6G	910 231 6G	910 237 6G	910 242 6G
		€	1045.00	1525.00	1995.00	2350.00	2690.00	3390.00
paint	flame red	Ref.	908 883 6G	908 889 6G	910 227 6G	910 233 6G	910 239 6G	910 245 6G
	RAL 3000	€	769.00	1045.00	1175.00	1525.00	1795.00	2190.00
paint	light blue	Ref.	908 884 6G	908 890 6G	910 229 6G	910 234 6G	910 240 6G	910 246 6G
	RAL 5012	€	769.00	1045.00	1175.00	1525.00	1795.00	2190.00
paint	mouse grey	Ref.	523 338 6G	523 339 6G	523 340 6G	523 341 6G	523 342 6G	523 343 6G
	RAL 7005	€	769.00	1045.00	1175.00	1525.00	1795.00	2190.00
paint	reseda green	Ref.	908 885 6G	910 224 6G	910 230 6G	910 235 6G	910 241 6G	910 247 6G
	RAL 6011	€	769.00	1045.00	1175.00	1525.00	1795.00	2190.00
paint	yellow orange	Ref.	908 882 6G	908 888 6G	910 226 6G	910 232 6G	910 238 6G	910 243 6G
	RAL 2000	€	769.00	1045.00	1175.00	1525.00	1795.00	2190.00
Accessories								
Oilproof and watertight models, factory fitted only	Ref.		910 248 6G	910 248 6G	910 248 6G	910 249 6G	910 249 6G	910 249 6G
	€		79.90	79.90	79.90	104.90	104.90	104.90
Hinged lids, can be fitted later	Ref.		910 257 6G	910 258 6G	910 259 6G	910 261 6G	910 262 6G	910 263 6G
	€		104.90	104.90	175.00	195.00	245.00	259.00

Wheel Ø: 180 mm. Wheel type: nylon.
Wheel fittings: 2 swivel castors with
1 x stops, 2 fixed castors. Overall
height: 220 mm. Max. load: 1350 kg. Max.
load / castor: 450 kg.

7| **Ref. 739 031 6G € 189.00**

- With robust roller system
- Tilting at any height via rope pull from driver's seat
- Secured against unintentional slipping and tilting

Max. load: 1000 kg. Overall length: 1420 mm. Overall height: 1070 mm. Height of front edge: 1070 mm. Type: with forklift pockets. Fork pocket dimensions: 200 x 90 mm. Forklift pocket spacing: 600 mm. Material: sheet steel. Material thickness: 3 mm.

For volume: 0,15 – 1,0 m³. Wheel
Ø: 180 mm. Wheel type: nylon.
Wheel fittings: 2 swivel castors
with 1 x stops, 2 fixed castors.
Overall height: 220 mm. Max. load /
castor: 350 kg.

8| **Ref. 927 122 6G € 189.00**

Please ask for details.



**Video
Online!**

			9	10	11
Capacity	m³		0.5	0.75	1
Overall width	mm		1008	1190	1560
Finish	Colour				
hot dip galvanised	hot dip galvanised	Ref.	730 458 6G	730 460 6G	730 461 6G
		€	1045.00	1225.00	1295.00
painted	flame red RAL 3000	Ref.	730 455 6G	730 456 6G	730 457 6G
		€	799.00	1045.00	1145.00