

11–12 | ERGOBJÖRN TT-05 electric tow trucks

- Driver attendance check
- Comfort support rail
- Powerful 800 W motor

Weight: 160 kg. Tensile force: 500 kg. Overall length: 1425 mm. Overall width: 693 mm. Trailer load: 500 kg. Frame material: sheet steel. Climbing capability: 7 %. Voltage: 24 V. Pulling/pushing speed under load: 10,5 km/h. Wheel fittings: pneumatic tyres. Steering wheel diameter: 260 mm. Steering wheel width: 85 mm. Fixed wheel diameter: 320 mm.

11 | Frame colour: red.

Ref. 499 163 6G € 9000.00

12 | Frame colour: white.

Ref. 499 164 6G € 9000.00

 **More products online!**



Complete with coupling and 24 V, 14 A battery charger.

13 | Puncture proof tyres, extra cost

Wheel Ø: 320 mm. Material: solid rubber, non-marking. Roller Ø: 260 mm.

13 | Ref. 499 167 6G € 289.00

16–17 | High performance charging devices

16 | Strength of current: 16.5 A.

Ref. 499 171 6G € 1195.00

17 | Strength of current: 20 A.

Ref. 499 173 6G € 1195.00

14–15 | TT-05 trailer

Frame material: sheet metal / steel. Overall length: 1352 mm. Loading height: 360 mm. Platform length: 845 mm. Platform width: 643 mm. Platform material: sheet metal. Max. load: 200 kg. Wheel type: pneumatic tyres. Wheel Ø: 260 mm. Wheel bearing: ball bearing. Wheel width: 85 mm.

15 | Colour: red.

Ref. 499 126 6G € 919.00

14 | Colour: white.

Ref. 499 127 6G € 919.00



18 | TAKKTOR electric tow trucks

- Secured against unauthorised start-up
- Emergency off switch on the drawbar arm joint
- Coupling height 85 – 380 mm

Weight: 315 kg. Overall length: 740 mm. Overall width: 590 mm. Overall max. load: 2000 kg. Frame material: steel. Frame colour: charcoal RAL 7016 / lemon yellow RAL 1012. Wheel fittings: 2 drive wheels, 2 swivel castors. Steering wheel material: polyurethane. Steering wheel diameter: 100 mm. Steering wheel width: 32 mm. Running

wheel material: elastic. Fixed wheel diameter: 260 mm. Type of brakes.

18 | Ref. 494 416 6G € 6100.00



EUROKRAFT
pro
by KAISER+KRAFT



Video Online!



19–20 | Clip-on coupling system

Material: steel. Finish: zinc plated by galvanization. Length: 1450 mm. Width: 190 mm. Height: 680 mm.

19 | Ref. 499 524 6G € 389.00

20 | Minimum order quantity: 2.

Ref. 499 527 6G € 379.00

21–22 | Mobile Kanban shelf units


- Complete with 2 mesh shelves
- Non-slip articulated feet, height adjustable
- Platform tilts 0°, 8° and 16°

Max. load: 500 kg. Platform length: 1208 mm. Platform width: 808 mm. Length: 1280 mm. Width: 810 mm. Height: 1705 mm. Number of levels: 2. Max. load per platform: 200 kg. Material: steel. Colour: charcoal RAL 7016. Adjustment pattern for internal shelves: 150 mm. Loading height: 125 mm. Weight: 77 kg. Platform material: steel.

22 | Ref. 499 523 6G € 1075.00

21 | Minimum order quantity: 2.

Ref. 499 526 6G € 1025.00

 Available in most RAL colours. Only 10% extra.

EUROKRAFT
pro
by KAISER+KRAFT



Video Online!

23–24 | Wire mesh shelves

Width: 808 mm. Length: 1208 mm. Max. load: 200 kg. Material: steel. Colour: charcoal RAL 7016. Finish: powder coated. Thickness: 50 mm.

23 | Ref. 499 525 6G € 199.00

24 | Minimum order quantity: 5.

Ref. 499 528 6G € 189.00



Forklift pockets 240 x 80 mm, fork entry clearance 350 mm.