

## UNI and MULTI tanks

### For storing new and used oil, heating oil and diesel

- For new and used oil, diesel / heating oil, flash point > 55 °C
- Also approved for use in water protection zones and buildings without sump tray (observe country specific laws)
- Low overall height – no steps required when filling (up to 1000 litres)
- Integrated, zinc plated sheet steel sump tray
- Includes fill level indicator, optical leak indicator, integrated carrying handles

Double walled tanks made of zinc plated sheet steel with PE inner container (HDPE).

Storage tanks may only be set up inside buildings (two abutting walls with roof).



### UNI – storage tank

Only approved for internal transport. With steel base pallet for forklift access on long side.

### MULTI – storage and transport tank

- Approved for on-site and off-site transport according to ADR (without pump attached)
- Mandatory inspection required every 2.5 years (ADR 6.5.4.4.1b) – transport approval for PE tank is valid for 5 years
- Low centre of gravity increases stability and improves handling and transport

With permanently attached sheet steel pallet, accessible from four sides with forklift or pallet truck.

### All storage tanks on this page



Capacity	l	400	750	1000	1500
Length x width x height	mm	730 x 700 x 1170	980 x 770 x 1460	1280 x 800 x 1470	1640 x 800 x 1870
UNI – storage tank	Ref.	978 189-2G	977 862-2G	977 863-2G	977 864-2G
	€	479,-	619,-	749,-	1.295,-
MULTI – storage and transport tank	Ref.	977 865-2G	977 866-2G	977 867-2G	977 868-2G
	€	599,-	739,-	929,-	1.495,-



**5**  
Year  
guarantee



from € **479,-**



Accessories	Ref.	€
1 GRP filling bowl	977 869-2G	225,-
Suction tube with tank coupling for tanks up to 1000 litres	977 871-2G	125,-
2 Suction tube with tank coupling for tanks up to 1500 litres	605 324-2G	149,-
3 Manual piston pump for storage tanks, suction tube/hose length 1640 mm, pump rate 0.25 l/stroke. Only suitable for diesel and oils.	611 671-2G	109,-
4 Hose for hand piston pump, electrically conductive, length 1.5 m	598 909-2G	21,90
5 Electric drum pump 230 V, pump rate 35 l/min. Only suitable for diesel and heating oil.	118 445-2G	275,-
6 Flow meter, electronic for uncalibrated applications	118 444-2G	199,-

## CUBE tank systems

### For diesel, AdBlue® (AUS32) and used oil

- With hinged lid – approved for use in indoor and outdoor areas
- Complete with accessories installed
- General certification Z-40.21-510

Integrated sump tray, optical leak indicator, ventilation cap, fill level indicator.

All components are optimally integrated and protected. No protruding, awkward parts – optimum handling.

### Diesel tank

230 V electric pump, volumetric flow meter, hose reel with 8 m hose, automatic pump pistol with holster, filling connection with tank coupling and limit indicator, filter with water separator. Lid colour orange.

### AdBlue® tank

230 V electric pump, volumetric flow meter, hose reel with 8 m hose, automatic pump pistol with holster, filling connection with 2" dry coupling, overflow protection, fan heater for valves and controls (winter). Lid colour blue.

### Used oil tank

Funnel with dirt strainer, drainage surface, suction tube with tank coupling, additional 1" and 2" connections. Lid colour orange.



**10**  
Year  
guarantee



on  
the  
tank

For outdoor



Used oil tank

Diesel tank

Capacity	l	1000	1500	2500
Length x width x height	mm	1200 x 800 x 1800	1200 x 1150 x 1800	1200 x 1800 x 1800
Diesel tank	Ref.	123 782-2G	123 761-2G	123 778-2G
	€	2.990,-	3.150,-	3.550,-
AdBlue® tank	Ref.		123 774-2G	123 775-2G
	€		5.400,-	5.800,-
Used oil tank	Ref.	123 171-2G	123 172-2G	123 173-2G
	€	1.725,-	2.150,-	2.590,-

YELLOW =  
7 working days

**FREE DELIVERY**  
**SALES FAX: 1 800 677 301 (local rate)**

**KAISER + KRAFT**  
EVERYTHING FOR THE BUSINESS.

ENVIRONMENT