Justrite

1–6| Small FM safety cupboards

- For the storage of flammable and water hazardous liquids according to FM (please observe country-specific regulations)
- Effective storage directly at the workstation
- Quick, direct access to frequently used media

Material: sheet steel, powder coated. Hazard class: for water hazardous liquids in GHS categories 1 – 4. Body colour: yellow. Door colour: yellow. Lock type: three point locking. Number of shelves: 1. Shelf material: sheet steel, galvanised. Number of sump trays: 1.

These cupboards are not approved for the storage of flammable media in Germany, Switzerland, Austria, the Netherlands, Belgium, and Luxembourg.

Please observe the regulations and requirements binding for your country.

Please contact your responsible authority to determine approval for your application.

		1	2	3	4	5	6
External width	**mm**	**432**	**432**	**591**	**591**	**889**	**889**
External height	mm	559	559	889	889	889	889
External depth	mm	432	432	457	457	559	559
Internal width		349					
Internal height		470					
Internal depth		349					
Door type		hinged door	hinged door	hinged door	hinged door	hinged doors	hinged doors
Door version		manual	self-closing	manual	self-closing	manual	self-closing
Number of doors	pcs.	1	1	1	1	2	2
Shelf height adjustment increments	mm			76	76	76	76
Base sump tray capacity	l	6	6	10	10	18.5	18.5
	Ref.	424 758 6G	424 760 6G	424 762 6G	424 764 6G	424 767 6G	424 769 6G
	€	**629.00**	**1025.00**	**979.00**	**1045.00**	**1095.00**	**1545.00**
Accessories							
Shelves	Ref.	516 574 6G	516 574 6G	516 576 6G	516 576 6G	516 578 6G	516 578 6G
	€	**42.90**	**42.90**	**59.90**	**59.90**	**69.90**	**69.90**

7–8| Fire resistant hazardous goods wall-mounted cupboards type 30

- For regulation compliant storage of small quantities of flammable liquids in workshops in accordance with EN 14470-1 and TRGS 510
- Flammable liquids such as spray cans, paints, etc. can be stored safety directly at the workstation – e.g. above the worktop
- Quick access – saves time and ensures safety at the workplace

External width: 995 mm. External height: 482 mm. External depth: 470 mm. Internal width: 942 mm. Internal height: 414 mm. Internal depth: 419 mm. Material: sheet steel, powder coated. Hazard class: for flammable media in work rooms in accordance with DIN EN 14470-1 and TRGS 510 (appendix 3). Fire resistance: 30 minutes. Ventilation: ventilation connection (NW 75). Weight: 76.68 kg. Body colour: charcoal RAL 7016. Door colour: charcoal RAL 7016. Door type: hinged doors. Number of doors: 2. Number of sump trays: 1. Base sump tray capacity: 5 l.

Lock type: profile cylinder lock.

7| **Ref. 118 466 6G € 1145.00**

Lock type: without lock.

8| **Ref. 118 465 6G € 1025.00**

9| Shelves

Material: sheet steel. Max. load: 75 kg. Weight: 6 kg.

9| **Ref. 118 468 6G € 67.90**

Product Reference = Ex Stock / Fast Delivery. Actual delivery times online.
Prices subject to change.