



1



NEW

1 | FR 60 safety storage cupboards for rechargeable batteries

- For the safe storage and provision of lithium batteries/rechargeable batteries
- MPA-tested fire resistance for more than 60 min from the inside to the outside in accordance with EN 1363-1, successful practical explosion test by an independent testing institute
- With smoke detector, fire protection seals, closure system to seal cold smoke in

height: 520 mm. External depth: 660 mm. Internal width: 730 mm. Internal height: 450 mm. Internal depth: 530 mm. Fire resistance: 60 minutes. Weight: 105 kg. Body colour: grey. Door colour: orange. Door type: hinged doors. Lock type: cylinder lock. Number of doors: 2. For media: lithium-ion batteries/rechargeable batteries.

1 | Ref. 570 497 6G € 1875.00

External width: 800 mm. External



4



NEW

2-4 | FR 60 safety battery charging cabinets

- Safety for particularly dangerous charging of lithium batteries/ rechargeable batteries, most often the cause of fires
- MPA-tested fire resistance for more than 60 min from the inside to the outside in accordance with EN 1363-1, successful practical explosion test by an independent testing institute
- Simultaneous charging of several rechargeable batteries in the cabinet, separate charging and storage

External height: 520 mm. External depth: 660 mm. Internal width: 730 mm. Internal height: 450 mm. Internal depth: 530 mm. Fire resistance: 60 minutes. Weight: 106 kg. Body colour: grey. Door colour: orange. Door type: hinged doors. Lock type: cylinder lock. Number of doors: 2. For media: lithium-ion batteries/rechargeable batteries.



5

5 | Fireproof cable outlets

Colour: grey. Height: 200 mm. Width: 200 mm. Depth: 25 mm.

5 | Ref. 570 504 6G € 119.00

	2	3	4
External width mm	800	800	890
Fittings	smoke detector, power supply in cupboard, forced ventilation, electrical isolation when heat builds up, door contact switch	smoke detector with floating contact for alarm signal, power supply in cupboard, forced ventilation, electrical isolation when heat builds up, door contact switch, alarm function, electrical isolation also when smoke forms	smoke detector with floating contact for alarm signal, power supply in cupboard, forced ventilation, electrical isolation when heat builds up, door contact switch, with remote alarm function and data transfer using SIM card, additional functions using remote access, electrical isolation also when smoke forms
Ref.	570 499 6G on request	570 501 6G on request	570 503 6G on request