



Anti-fatigue



Slip resistant

1–5 | Anti-fatigue matting

- Classic matting for work at conveyor belts, production lines and order picking
- Non-slip (R10) in accordance with DIN 51130
- Reduces symptoms of fatigue

Height: 9 mm. Material: PVC. Temperature resistance: 0 °C to +60 °C. Weight: 3.5 kg/m². Type: single-ply. Feature: non-slip / anti-fatigue / tapered. Work area: dry. Surface: closed.

			1	2	3	4	5
Width	mm		600	900	900	900	900
Length			900		1500	18300	18300
Max. roll length	m			18.3			
Weight	kg		3	3	7	30	50
Colour	Minimum order quantity						
black	1 m	Ref. €		502 655 6G 62.90			
black	1 pcs.	Ref. €	716 807 6G 42.90		716 808 6G 139.00		716 809 6G 1275.00
black	1 m	Ref. €		502 657 6G 89.90			
black	1 pcs.	Ref. €	716 810 6G 59.90		716 811 6G 135.00		716 813 6G 1375.00
grey	1 m	Ref. €		502 656 6G 62.90			
grey	1 pcs.	Ref. €	716 803 6G 42.90		716 805 6G 139.00	716 806 6G 1275.00	



Anti-fatigue



Fire retardant

6–7 | Anti-fatigue matting, flame retardant

- Reduce symptoms of fatigue at standing workstations
- Fire protection class B1 in accordance with DIN 4102
- Ergonomic matting with studded, closed surface

Height: 15 mm. Material: polyurethane. Temperature resistance: 0 °C to +60 °C. Colour: black. Weight: 5.2 kg/m². Feature: anti-fatigue / flame retardant / tapered. Work area: dry. Surface: closed. Custom dimensions possible.

6 | Width: 600 mm. Length: 900 mm. Weight: 4.5 kg. Weight per item: 2.25 kg. Pack of: 2.

Ref. 906 799 6G € / pack 299.00

7 | Width: 900 mm. Length: 1200 mm. Weight: 9 kg. Weight per item: 9 kg.

Ref. 906 800 6G € 299.00

Other sizes available on request.



Anti-fatigue



Slip resistant



For wheeled traffic

8–10 | Anti-fatigue matting, can be used on both sides

- R10 non-slip protection in accordance with EN 13552
- Good drainage characteristics
- Resistant to mild acids and alkalis

Height: 12 mm. Material: vinyl. Temperature resistance: -20 °C to +60 °C. Colour: black / yellow. Weight: 5 kg/m². Max. load: 2000 kg/m². Feature: non-slip / anti-fatigue / can be driven on / tapered. Work area: wet / dry. Surface: open. Custom dimensions possible.

8 | Width: 600 mm. Length: 1200 mm. Weight: 5 kg.




Ref. 722 212 6G € 159.00

9 | Width: 1000 mm. Length: 1500 mm. Weight: 9 kg.

Ref. 722 217 6G € 299.00

10 | Width: 1200 mm. Length: 1800 mm. Weight: 13 kg.

Ref. 722 223 6G € 369.00



Products cut to order may exhibit dimensional tolerances of up to ±5% depending on the material. Products cut to order are produced specifically for you, and can therefore not be returned.

11–12 | Anti-fatigue matting, can be used on both sides

- R10 non-slip protection in accordance with EN 13552
- Good drainage characteristics
- Resistant to mild acids and alkalis

Width: 900 mm. Height: 12 mm. Material: vinyl. Temperature resistance: -20 °C to +60 °C. Max. roll length: 10 m. Weight: 5 kg/m². Feature: non-slip / anti-fatigue / can be driven on. Work area: wet / dry. Surface: open. Custom dimensions possible.

		11	12
Weight	kg	5	7
Max. load	kg/m ²	2000	5000
Colour			
black	Ref. € / m	908 998 6G 139.00	908 999 6G 189.00
blue	Ref. € / m	908 994 6G 139.00	908 995 6G 189.00
green	Ref. € / m	908 996 6G 139.00	908 997 6G 189.00