WORKSHO

6 | Mini air ratchets

- Fully sealed head prevents swarf or similar chips from entering. Low vibration
- · Short design

Max. operating pressure: 6.3 bar. Length: 150 mm. Noise level: 90 dB(A). Weight: 0.55 kg.

6 | Ref. 570 554 6G € 195.00







Made in Germany

7| HiPer 3HP fine tooth reversible ratchets

- A huge amount of extra force in comparison to ratchets with comparable dimensions
- Locking function of the shift lever provides protection against accidental reversal
- Service life increased by the use of the latest lubricants in the ratchet

mechanism

Weight: 0.08 kg. Type: with ball lock. Length: 116 mm. Conforms to: DIN 3122, ISO 3315.

7| Ref. 570 553 6G € 59.90

8| MINI TWIN turbo extra short impact wrenches

- Exhaust air is guided downwards through the handle
- Low vibration and easy operation
- Innovative 8-blade air motor with 25% higher impact performance ensures maximum torques

Type: two-level (clockwise), one-level (anti-clockwise). Max. operating

8 | Ref. 570 555 6G € 245.00

level: 92.5 dB(A). Weight: 1.64 kg.

pressure: 6.3 bar. Noise

10| HiPer 6HP fine tooth reversible ratchets

- Low manufacturing tolerances prevent dirt from entering
- High quality, easy to clean, corrosion resistant
- Suspension option integrated in the handle

Weight: 0.62 kg. Type: with ball

lock. Handle: 2-component handle. Length: 275 mm. Conforms to: DIN 3122, ISO 3315. Square drive in inches: 1/2. Tooth: 90.

10 | **Ref. 570 552 6G € 74.90**

9 Hose reels

Area of application: commercial vehicle. Hose length: 15 m. Length: 378 mm. Width: 459 mm.

9 | Ref. 570 548 6G € 245.00



11-12| Torque wrenches

- Designed for demanding use in the workshop
- Wide range of uses for controlled tightening of screws when changing tyres, bicycle, passenger vehicle and commercial vehicle applications and diverse applications in industry and trades
- Optimised sealing ring for protection from foreign particles

Actuation accuracy: ±3%. Conforms to: DIN 3120.

Weight: 0.41 kg. Width: 24 mm. Length: 234 mm. Square drive in inches: 1/4. Tooth: 20.

12 | Ref. 570 550 6G € 245.00

Weight: 1.16 kg. Width: 44 mm. Length: 519 mm. Square drive in inches: 1/2. Tooth: 32.

11 | Ref. 570 551 6G € 239.00



Endurance testing of the HAZET torque wrenches from the 5000 and 6000 series demonstrated that turning them back to the smallest scale value is no longer required.