

13–18 | Machine steps with ribbed aluminium sheet metal steps

- Welded aluminium pipe construction
- Non-slip plastic feet
- Top step 550 x 300 mm

Step depth: 225 mm. Step width: 550 mm. Access: single sided. Platform width: 550 mm. Platform depth: 300 mm. Frame material: aluminium. Material of treads: aluminium, ribbed.

15
Year
Guarantee

Intertek
Deutschland **Bauart
geprüft**



		13	15	16	17	18
Steps incl. platform	pcs.	1	2	3	4	5
Platform height	mm	200	400	600	800	1000
Overall depth	mm	370	620	880	1130	1390
Overall width	mm	590	700	750	790	840
	Ref.	294 640 6G	128 872 6G	128 880 6G	128 899 6G	128 902 6G
	€	139.00	229.00	369.00	469.00	589.00

14 | Wheel sets with 4 sprung castors with brakes

Wheel Ø: 50 mm. Wheel fittings: 4 castors which brake under load. Pack of: 4.

**14 | Ref. 945 278 6G
€/pack 275.00**

For steps with 2 – 5 individual steps.

19 | Adjustable feet

Plate diameter: 80 mm. Height adjustment range: 70 mm. Weight: 2 kg. Weight per item: 0.5 kg. Pack of: 4.

**19 | Ref. 945 279 6G
€/pack 104.90**

20–22 | Mobile machine steps

- Extremely safe due to 600 mm high hand rail on one side
- Mobile on 2 fixed castors
- Welded, aluminium tubular struts

Step depth: 225 mm. Platform width: 550 mm. Platform depth: 300 mm. Frame material: aluminium. Material of treads: aluminium, ribbed. Wheel fittings: 2 fixed castors. Wheel Ø: 125 mm.

15
Year
Guarantee

Intertek
Deutschland **Bauart
geprüft**

		20	21	22
Steps incl. platform	pcs.	3	4	5
Platform height	mm	600	800	1000
Overall depth	mm	870	1130	1390
Overall width	mm	750	800	840
	Ref.	760 795 6G	760 796 6G	760 797 6G
	€	469.00	599.00	779.00

**More products
online!**



20



23–27 | Machine steps with aluminium safety steps

- Treads with certified anti-slip surface R13
- Welded aluminium pipe construction
- Non-slip plastic feet

Platform width: 550 mm. Platform depth: 300 mm. Frame material: aluminium. Material of treads: aluminium. Type: certified R13 slip resistance.

19 | Adjustable feet

Plate diameter: 80 mm. Height adjustment range: 70 mm. Weight: 2 kg. Weight per item: 0.5 kg. Pack of: 4.

19 | Ref. 945 279 6G €/pack 104.90

14 | Wheel sets with 4 sprung castors with brakes

Wheel Ø: 50 mm. Wheel fittings: 4 castors which brake under load. Pack of: 4.

14 | Ref. 945 278 6G €/pack 275.00

For steps with 2 – 5 individual steps.

		23	24	25	26	27
Steps incl. platform	pcs.	1	2	3	4	5
Platform height	mm	200	400	600	800	1000
Overall depth	mm	370	650	880	1140	1340
Overall width	mm	590	700	750	790	830
	Ref.	453 576 6G	453 577 6G	453 578 6G	453 579 6G	453 580 6G
	€	265.00	479.00	659.00	799.00	989.00

15
Year
Guarantee



25



23



24