

1–2 | Professional aluminium working platforms

- Particularly robust construction
- Low weight – easy to transport
- Large working platform – plenty of space for user and materials

Platform width: 290 mm.

Feature: folding. Access: double sided.

Frame material: aluminium. Height

folded: 110 mm. Max. load: 150 kg.

1 | Platform length: 1300 mm. Platform height: 500 mm. Overall length: 1640 mm. Overall width: 460 mm. Length folded: 1300 mm. Width folded: 450 mm. Steps incl. platform: 2 x 2. Weight: 7.9 kg. Working height: 2500 mm.

Ref. 111 400 6G € 409.00

2 | Platform length: 1740 mm. Platform height: 700 mm. Overall length: 2330 mm. Overall width: 700 mm. Length folded: 1740 mm. Width folded: 700 mm. Steps incl. platform: 2 x 3. Weight: 7.5 kg. Working height: 2700 mm.

Ref. 486 100 6G € 499.00



Ideally suited for use in industry and trade.

15
Year
Guarantee

Intertek
Deutschland

Bauart
geprüft

altrex



5
Year
Guarantee



Ideal for occasional use.

3 | Aluminium working platforms

- Comfortable work due to a large platform area
- Excellent stability due to double locking
- Easy to transport due to low inherent weight

Platform length: 725 mm. Platform width: 300 mm. Platform height: 500 mm. Feature: folding. Access: single sided. Overall length: 950 mm. Overall width: 395 mm. Overall height: 500 mm. Frame material: aluminium. Length folded: 800 mm. Width folded: 395 mm. Height folded: 145 mm. Steps incl. platform: 2 x 2. Step width: 295 mm. Material of treads: aluminium. Weight: 4.2 kg. Working height: 2500 mm. Max. load: 150 kg.

3 | **Ref. 480 440 6G € 82.90**



5

11



EUROKRAFT
pro
by KAISER+KRAFT



Height adjustable threaded feet

4–7 | Working platforms

- Sturdy and durable angled steel frame
- Easy height adjustment using threaded feet
- Optionally powder coated in light blue RAL 5012 or hot dip galvanised

Platform height: 165 – 230 mm. Frame material: steel. Platform width: 610 mm. Max. load: 150 kg.

Supplied flat pack – easy self-assembly.

			4	5	6	7
Platform length	mm		610	910	1210	1510
Frame Type	colour					
hot dip galvanised	with mesh plate	Ref.	476 210 6G	476 216 6G	476 222 6G	476 228 6G
		€	499.00	659.00	879.00	1025.00
hot dip galvanised	with phenolic plywood panel	Ref.	476 211 6G	476 217 6G	476 223 6G	476 229 6G
		€	359.00	449.00	599.00	699.00
hot dip galvanised	with ribbed rubber plate	Ref.	476 212 6G	476 218 6G	476 224 6G	476 230 6G
		€	389.00	489.00	659.00	759.00
light blue RAL 5012	with mesh plate	Ref.	476 207 6G	476 213 6G	476 219 6G	476 225 6G
		€	469.00	589.00	819.00	799.00
light blue RAL 5012	with phenolic plywood panel	Ref.	476 208 6G	476 214 6G	476 220 6G	476 226 6G
		€	359.00	419.00	529.00	659.00
light blue RAL 5012	with ribbed rubber plate	Ref.	476 209 6G	476 215 6G	476 221 6G	476 227 6G
		€	359.00	419.00	549.00	699.00

8–11 | Working platforms

- Sturdy and durable angled steel frame
- Easy height adjustment using threaded feet
- Optionally powder coated in light blue RAL 5012 or hot dip galvanised

Platform height: 255 – 320 mm. Frame material: steel. Platform width: 610 mm. Max. load: 150 kg.

Supplied flat pack – easy self-assembly.

			8	9	10	11
Platform length	mm		610	910	1210	1510
Frame Type	colour					
hot dip galvanised	with mesh plate	Ref.	476 234 6G	476 240 6G	476 246 6G	476 252 6G
		€	499.00	669.00	889.00	1025.00
hot dip galvanised	with phenolic plywood panel	Ref.	476 235 6G	476 241 6G	476 247 6G	476 253 6G
		€	369.00	459.00	599.00	719.00
hot dip galvanised	with ribbed rubber plate	Ref.	476 236 6G	476 242 6G	476 248 6G	476 254 6G
		€	389.00	489.00	659.00	769.00
light blue RAL 5012	with mesh plate	Ref.	476 231 6G	476 237 6G	476 243 6G	476 249 6G
		€	479.00	619.00	829.00	949.00
light blue RAL 5012	with phenolic plywood panel	Ref.	476 232 6G	476 238 6G	476 244 6G	476 250 6G
		€	339.00	419.00	529.00	669.00
light blue RAL 5012	with ribbed rubber plate	Ref.	476 233 6G	476 239 6G	476 245 6G	476 251 6G
		€	359.00	459.00	599.00	719.00