

EUROKRAFT



Intertek Deutschland Bauart geprüft

15 Year guarantee

from € **139,-**



With non-slip, ribbed steps, 80 mm deep



Steps with cushioned front edges

Step ladders, single sided

- Professional quality – ideal for daily use
- Robust aluminium construction
- Very safe conical construction
- Extra strong safety hinges
- Reinforced rails – exceeds EN 131 requirements
- Solid safety platform 250 x 300 mm

Rails and steps made of extruded aluminium profiles. Permanent multiple bell end type fitting of rungs. High torsion resistance. Step spacing 235 mm.

7 steps and above with high strength tension straps. With large storage tray.

1 Standard model

With 80 mm deep, ribbed steps and non-slip ladder feet.

2 Cushioned model

Steps with cushioned front edges. The padded front edges provide comfort for shins and knees when leaning and ensures particularly secure and comfortable footing.

Steps incl. platform		3	4	5	6	8	10	12
Platform height	mm	665	905	1145	1375	1845	2315	2785
Overall height	mm	1345	1575	1805	2045	2515	2985	3455
1 without cushioned steps	Weight	kg	5.5	6.6	7.7	8.7	10.5	13.5
	Ref.		945 299-1G	945 300-1G	945 301-1G	945 302-1G	945 303-1G	945 304-1G
	€		139,-	169,-	179,-	199,-	279,-	339,-
2 with cushioned steps	Weight	kg	5.9	7.2	8.1	9.5	12.5	14.8
	Ref.		945 306-1G	945 308-1G	945 309-1G	945 310-1G	945 311-1G	945 312-1G
	€		169,-	195,-	245,-	279,-	349,-	399,-



Intertek Deutschland Bauart geprüft

15 Year guarantee



With ergo-pad®



With four load-dependent braked castors

3 Comfort model

With ergo pad® for optimum carrying comfort as well as easy and safe handling. Non-slip nivello® safety feet.

4 Mobile model

With four practical, self-locking braked castors, Ø 80 mm, and non-slip nivello® safety feet. The load dependent braked castors enable smooth movement when there is no load on the ladder and secure standing when the ladder is under load.



3 With ergo pad®

- Non-slip, ergonomically shaped handle grip made of soft plastic for carrying comfort and safe handling
- Attached at optimum carrying point, safe carrying at load centre
- Clamping mechanism secures ladder struts when folded

3 + 4 With nivello® feet

- 4x larger contact surface
- Flexible adaptation to floor
- Best adhesion to floor

Steps incl. platform		3	4	5	6	8	10	12
Platform height	mm	700	930	1170	1400	1870	2340	2810
Overall height	mm	1370	1600	1830	2070	2540	3010	3480
3 with ergo-pad®	Weight	kg	5.5	6	7	8	10	11.9
	Ref.		945 314-1G	671 576-1G	671 584-1G	671 592-1G	671 606-1G	737 087-1G
	€		165,-	159,-	175,-	199,-	299,-	369,-
4 with castors	Weight	kg	7.5	7.9	8.5	9.6	12.4	15.1
	Ref.		609 054-1G	609 055-1G	609 057-1G	609 058-1G	609 060-1G	609 062-1G
	€		369,-	439,-	419,-	449,-	529,-	599,-

YELLOW = 7 working days

FREE DELIVERY
SALES FREE FAX: 1 800 677 301 (local rate)

KAISER+KRAFT
EVERYTHING FOR THE BUSINESS.