

**EUROKRAFT**

★★★★★

Intertek Deutschland Bauart geprüft

**15**  
Year  
guarantee



1



2



1 - 4

With solid hinge, each bolted at four points



1 - 4

With non-slip, ribbed steps, 80 mm deep



2

Steps with cushioned front edges

## Step ladders, double sided

- Professional quality – ideal for daily use
- Robust aluminium construction
- Stable, secure stand due to conical construction
- Extra strong safety hinges bolted at four points
- Reinforced rails – exceeds EN 131 requirements

Rails and steps made of extruded aluminium profiles. Permanent multiple bell end type fitting of rungs. High torsion resistance. Step spacing 235 mm. High strength tension straps.

### 1 Standard model

With 80 mm deep, ribbed steps and non-slip ladder feet.

### 2 Cushioned model

Steps with cushioned front edges. The padded front edges provide comfort for shins and knees when leaning and ensures particularly secure and comfortable footing.

**Step ladders with non-slip tread inserts can be found on page 741.**

Steps incl. platform		2 x 3	2 x 4	2 x 5	2 x 6	2 x 8	2 x 10	2 x 12	
Vertical height	mm	665	905	1135	1375	1845	2315	2775	
Working height	mm	2225	2475	2725	2975	3475	3975	4475	
1 without cushioned steps	Weight	kg	3.9	5.8	6.9	8.4	11.5	18.7	
	Ref.		945 316-2G	945 317-2G	945 318-2G	945 319-2G	945 320-2G	945 321-2G	945 322-2G
	€		109,-	129,-	165,-	209,-	275,-	299,-	329,-
2 with cushioned steps	Weight	kg	5	7.2	8.9	10.6	12.8	14.5	21.1
	Ref.		945 324-2G	945 325-2G	945 326-2G	945 327-2G	945 328-2G	945 329-2G	945 330-2G
	€		139,-	179,-	215,-	275,-	339,-	429,-	519,-



**15**  
Year  
guarantee

Intertek Deutschland Bauart geprüft

4

3



3

With ergo-pad®



4

With four load-dependent braked castors



### 3 Comfort model

With ergo pad® for optimum carrying comfort as well as easy and safe handling. Non-slip nivello® safety feet.

### 4 Mobile model

With four practical, self-locking braked castors, Ø 80 mm, and non-slip nivello® safety feet.

The load dependent braked castors enable smooth movement when there is no load on the ladder and secure standing when the ladder is under load.

### 3 With ergo pad®

- Non-slip, ergonomically shaped handle grip made of soft plastic for carrying comfort and safe handling
- Attached at optimum carrying point, safe carrying at load centre
- Clamping mechanism secures ladder struts when folded

### 3 + 4 With nivello® feet

- 4 x larger contact surface
- Flexible adaptation to floor
- Best adhesion to floor

Steps incl. platform		2 x 3	2 x 4	2 x 5	2 x 6	2 x 8	2 x 10	2 x 12	
Vertical height	mm	690	930	1160	1400	1870	2340	2790	
Working height	mm	2250	2500	2750	3000	3500	4000	4500	
3 with ergo-pad®	Weight	kg	4.5	5	7.5	9	12	15.5	18.7
	Ref.		612 006-2G	612 014-2G	612 022-2G	612 030-2G	612 049-2G	737 090-2G	945 332-2G
	€		125,-	149,-	185,-	215,-	255,-	359,-	469,-
4 with castors	Weight	kg	8.4	9.7	10.7	11.9	15.7	18	20.1
	Ref.		759 800-2G	759 801-2G	759 802-2G	759 803-2G	759 806-2G	759 808-2G	759 809-2G
	€		269,-	299,-	329,-	369,-	449,-	499,-	639,-

BLUE =  
14 working days