

## 1–6 | Professional rung ladders



- Steel hinges with extra reinforcement
- Rungs and rails made of high stability extruded aluminium profiles
- Ribbed rectangular rungs – very sturdy triple beaded rail/rung connection

Ladder type: step ladder. Access: double sided. Access type: rungs. Frame material: aluminium. Material of treads: aluminium with non-slip ribbed surface. Step depth: 30 mm. Feature: folding. Max. load: 150 kg.



		1	2	3	4	5	6
<b>Number of rungs</b>	pcs.	2 x 6	2 x 8	2 x 10	2 x 12	2 x 14	2 x 16
Vertical height	mm	1730	2300	2830	3370	3910	4450
Working height	mm	3000	3550	4050	4600	5100	5650
	Ref.	235 539 6G	235 547 6G	235 555 6G	235 563 6G	235 571 6G	235 598 6G
	€	215.00	285.00	329.00	389.00	439.00	549.00

## 7–12 | Professional rung ladders with nivello® ladder feet



- Professional quality – ideal for daily use
- Safety hinges made of zinc plated steel
- Reinforced rails – exceed EN 131 requirements

Ladder type: step ladder. Access: double sided. Access type: rungs. Frame material: aluminium. Material of treads: aluminium. Step depth: 30 mm. Feature: folding. Max. load: 150 kg.



Video Online!

		7	8	9	10	11	12
<b>Number of rungs</b>	pcs.	2 x 6	2 x 7	2 x 8	2 x 9	2 x 10	2 x 12
Vertical height	mm	1830	2010	2400	2700	2950	3510
Working height	mm	3050	3310	3580	3850	4110	4630
Standing height	mm	1050	1310	1580	1850	2110	2630
	Ref.	952 699 6G	517 275 6G	952 702 6G	737 091 6G	517 283 6G	737 092 6G
	€	269.00	299.00	319.00	389.00	389.00	459.00

## 13–17 | Plastic stepladders with aluminium steps



- Sturdy industrial design for daily use
- For working on electrical installations and in many chemical/pharmaceutical areas
- Permanently beaded step/rail connection

Ladder type: step ladder. Access: double sided. Access type: steps. Frame material: glass fibre reinforced plastic. Material of treads: aluminium, ribbed. Step depth: 80 mm. Feature: folding. Max. load: 150 kg.

		13	14	15	16	17
<b>Number of steps</b>	pcs.	2 x 4	2 x 6	2 x 8	2 x 10	2 x 12
Working height	mm	2500	3000	3500	4000	4500
Vertical height	mm	1100	1600	2100	2600	3100
	Ref.	486 096 6G	523 919 6G	523 920 6G	523 921 6G	523 922 6G
	€	329.00	439.00	539.00	689.00	749.00

## 18–22 | Solid plastic ladder with rungs



- Sturdy industrial design for daily use
- Rails and rungs made of GRP, without filling materials
- For working on electrical installations and in many chemical/pharmaceutical areas

Ladder type: step ladder. Access: double sided. Access type: rungs. Frame material: glass fibre reinforced plastic. Material of treads: glass fibre reinforced plastic. Step depth: 28 mm. Feature: folding. Max. load: 150 kg.

		18	19	20	21	22
<b>Number of rungs</b>	pcs.	2 x 4	2 x 6	2 x 8	2 x 10	2 x 12
Vertical height	mm	1270	1600	2100	2600	3510
Working height	mm	2500	3000	3500	4000	4500
	Ref.	486 090 6G	523 923 6G	523 924 6G	523 926 6G	486 092 6G
	€	479.00	689.00	849.00	1025.00	1095.00



**GUNZBURGER STEIGTECH**

Tested in accordance with EN 131.  
In compliance with EN 61478:2002 + A1:2004 (cat. 1:1000 V).



Tested in accordance with EN 131.  
In compliance with EN 61478:2002 (cat. 1:28000 V).

**GUNZBURGER STEIGTECHNIK**