



23–24 | Hook-in steps

Length: 250 mm. Width: 260 mm.

23 | Ref. 497 767 6G € 69.90

Length: 255 mm. Width: 300 mm.

24 | Ref. 497 766 6G € 52.90



25–27 | Entry level multi-purpose ladders

- Basic model at an amazing price
- Spread secured by very strong nylon belt and a rigid connecting brace
- Use on stairs possible (fitting included)

Ladder type: multi-purpose ladder. Access type: rungs. Frame material: aluminium. Rungs material: aluminium. Rung spacing: 280 mm. Rung depth: 30 mm. Max. load: 150 kg.

		25	26	27
Number of rungs	pcs.	3 x 7	3 x 8	3 x 10
Length as a lean-to ladder	mm	4270	5110	6520
Retracted length	mm	2030	2320	2880
Height as a step ladder	mm	2940	3490	4520
Ref.		944 207 6G	944 208 6G	944 209 6G
€		265.00	269.00	319.00

28–30 | Professional model multi-purpose ladders

- Professional model with solid steel fittings
- Rigid connecting brace with transport safety catch
- Sturdy cross beam for excellent stability

Ladder type: multi-purpose ladder. Access type: rungs. Frame material: aluminium. Rungs material: aluminium. Rung spacing: 280 mm. Rung depth: 30 mm. Max. load: 150 kg.

		28	29	30
Number of rungs	pcs.	3 x 7	3 x 9	3 x 12
Length as a lean-to ladder	mm	4870	6550	8510
Retracted length	mm	2070	2630	3470
Height as a step ladder	mm	3290	4330	5650
Ref.		944 212 6G	944 213 6G	944 214 6G
€		319.00	389.00	539.00
Accessories				
Fitting for use on stairs	Ref.	944 223 6G	944 223 6G	944 223 6G
€		36.90	36.90	36.90

31–32 | Industrial model multi-purpose ladders

- Extra thick rail construction for professional use in industrial applications
- Highly arched cross struts for particularly good stability, even on uneven ground
- Sturdy steel fittings and reinforced rails on first rung

Ladder type: multi-purpose ladder. Access type: rungs. Frame material: aluminium. Rungs material: aluminium. Rung spacing: 280 mm. Rung depth: 30 mm. Max. load: 150 kg.

		31	32
Number of rungs	pcs.	3 x 8	3 x 10
Length as a lean-to ladder	mm	5510	7220
Retracted length	mm	2430	3020
Height as a step ladder	mm	3950	4970
Ref.		944 215 6G	944 216 6G
€		499.00	629.00
Accessories			
Fitting for use on stairs	Ref.	944 223 6G	944 223 6G
€		36.90	36.90

33–36 | Industrial model multi-purpose ladders with wheel unit on top

- Extra thick rails for professional use in industrial applications incl. wheel unit on top
- Highly arched cross struts for particularly good stability, even on uneven ground
- Sturdy steel fittings with reinforced rails on first rung

Ladder type: multi-purpose ladder. Access type: rungs. Frame material: aluminium. Rungs material: aluminium. Rung spacing: 280 mm. Rung depth: 30 mm. Max. load: 150 kg.

		33	34	35	36
Number of rungs	pcs.	3 x 8	3 x 10	3 x 12	3 x 14
Length as a lean-to ladder	mm	5510	7220	8660	9780
Retracted length	mm	2430	3020	3630	4170
Height as a step ladder	mm	3950	4970	5800	6580
Ref.		944 218 6G	944 219 6G	944 221 6G	944 222 6G
€		469.00	629.00	729.00	869.00
Accessories					
Fitting for use on stairs	Ref.	944 223 6G	944 223 6G	944 223 6G	944 223 6G
€		36.90	36.90	36.90	36.90