

22–32 | Extension ladders and rope operated extension ladders

- Very sturdy, rectangular tubular rails
- High quality beading for permanent rung/rail connection
- Rectangular rungs ribbed on both sides for secure footing, 30 x 30 mm

Access type: rungs. Frame material: aluminium.
Max. load: 150 kg. Rail width: 25 mm. Rungs material: aluminium, ribbed. Rung depth: 30 mm.



		22	23	24	25	26	27	28	29	30	31	32
Number of rungs	pcs.	2 x 6	2 x 8	2 x 10	2 x 12	2 x 14	3 x 8	3 x 10	3 x 12	2 x 16	2 x 18	2 x 20
Ladder type		extending ladder	extending ladder	extending ladder	extending ladder	extending ladder	extending ladder	extending ladder	extending ladder	cable hoist ladder	cable hoist ladder	cable hoist ladder
Weight	kg	9	13.5	16.5	18.5	13.5	19.5	26.4	32.8	24.9	30.5	32.8
Width	mm	420	420	420	420	420	500	500	500	420	420	420
Working height	mm	4100	5200	6000	7200	8300	6900	8000	9700	9400	10300	11400
Cross beam width	mm		930	930	1200	1200	1200	1200	1200	1200	1200	1200
Extended length	mm	2960	4080	4920	6040	7220	5860	6980	8660	8340	9180	10300
Retracted length	mm	1940	2500	3060	3620	4140	2500	3060	3620	4740	5300	5860
Ref.		523 951 6G	480 553 6G	480 554 6G	480 555 6G	480 556 6G	480 558 6G	480 559 6G	480 560 6G	480 562 6G	480 563 6G	480 564 6G
€		199.00	409.00	479.00	529.00	659.00	529.00	659.00	759.00	859.00	969.00	1095.00

33–40 | Extending step ladders

- Secure footing due to 80 mm deep steps
- 1000 mm stile extensions for safe crossover
- Optionally available with clip-step R13 step tread cover

Ladder type: extending ladder. Access type: steps. Step depth: 80 mm. Feature: height adjustable / anti-slip.
Frame material: aluminium. Rung height: 85 mm. Max. load: 150 kg. Conforms to: EN 131.

NEW

		33	34	35	36	37	38	39	40
Number of steps	pcs.	7x1 + 5x1	9x1 + 6x1	11x1 + 7x1	14x1 + 7x1	7x1 + 5x1	9x1 + 6x1	11x1 + 7x1	14x1 + 7x1
Weight	kg	16.6	18.1	19.5	21.7	18.2	20.1	21.9	24.5
Working height	mm	3840	4650	5450	6200	3840	4650	5450	6200
Cross beam width	mm	930	930	1200	1200	930	930	1200	1200
Extended length	mm	3890	4730	5570	6410	3890	4730	5570	6410
Retracted length	mm	2490	3050	3610	4450	2490	3050	3610	4450
Type						with tread cover	with tread cover	with tread cover	with tread cover
Ref.		545 012 6G	545 014 6G	545 017 6G	545 019 6G	545 011 6G	545 013 6G	545 016 6G	545 018 6G
€		989.00	1025.00	1075.00	1195.00	1295.00	1325.00	1425.00	1595.00

33

41–44 | Telescopic lean-to ladders

- Triangular rails for ergonomic handling and higher stability
- 75° design provides an ideal angle of inclination
- Rungs with integrated dirt profiles for higher stability

material: anodised aluminium. Rungs material: aluminium. Rung depth: 50 mm. Conforms to: EN 131-6. Max. load: 150 kg.

Ladder type: lean to ladder. Access type: rungs. Frame

		41	42	43	44
Number of rungs	pcs.	10	13	11	13
Length as a lean-to ladder				3494	4085
Retracted length	mm	800	940	870	930
Feature			with beam	with stabilisers	with stabilisers
Ref.		490 709 6G	490 710 6G	569 024 6G	569 025 6G
€		439.00	489.00	419.00	439.00



42

41



WORKSHOP