



1–3 | Light safety railings

- Light safety railing for the demarcation of walkways and for guiding company internal traffic
- Space saving, can also be expanded and supplemented as required
- Easy bolt-together assembly, form-locking without protruding tabs or bolts

Overall length: 70 mm. Overall width: 70 mm. Overall height: 1000 mm. Colour: traffic yellow RAL 1023. Material: steel. Type of mounting: with base plate for bolting in place. Weight: 8 kg. Base plate length: 160 mm. Base plate width: 140 mm. Panel thickness: 3 mm. Base plate height: 10 mm. Height above ground: 1000 mm.

On request

Flexible model. Posts can be tilted up to 10°.

			1	2	3
Type			centre post	corner post	end post
Finish	Place of use				
hot dip galvanised and plastic coated	outdoor use	Ref.	116 287 6G	116 290 6G	116 285 6G
		€	209.00	215.00	179.00
plastic coated	indoor use	Ref.	116 286 6G	116 288 6G	116 284 6G
		€	155.00	159.00	125.00

4–7 | Bars for safety railing



- Light safety railing for the demarcation of walkways and for guiding company internal traffic
- Space saving, can also be expanded and supplemented as required
- Easy bolt-together assembly, form-locking without protruding tabs or bolts

Overall width: 40 mm. Overall height: 60 mm. Colour: traffic yellow RAL 1023. Material: steel. Type of mounting: for screw connection. Panel thickness: 3 mm. Tube form: square. Height above ground: 60 mm.

Easy installation:

Bolt posts in place, then bolt the rails to the posts using the special mounting technique.

Mounting material

and cover caps available on request.

			4	5	6	7
Overall length	mm		1000	1200	1500	2000
Finish	Place of use					
hot dip galvanised and plastic coated	outdoor use	Ref.	116 293 6G	116 295 6G	116 298 6G	116 301 6G
		€	109.00	139.00	159.00	239.00
plastic coated	indoor use	Ref.	116 291 6G	116 294 6G	116 296 6G	116 299 6G
		€	84.90	94.90	104.90	159.00



8–12 | Crash protection rails

- Optimum protection for inventory, machines, buildings, etc.
- Solid steel construction for maximum absorption of impact
- Can be adapted and extended to accommodate any object

Overall width: 40 mm. Overall height: 100 mm. Colour: traffic yellow RAL 1023. Material: steel. Type of mounting: for screw connection. Panel thickness: 3 mm.

			8	9	10	11	12
Overall length				1000	1200	1500	2000
Finish	Place of use						
hot dip galvanised, additionally powder coated	outdoor use	Ref.	518 761 6G	518 770 6G	518 771 6G	518 772 6G	518 773 6G
		€	175.00	139.00	175.00	185.00	239.00
powder coated	indoor use	Ref.	518 758 6G	518 762 6G	518 763 6G	518 764 6G	518 765 6G
		€	119.00	82.90	94.90	109.00	159.00

13 | Crash protection posts

- Optimum protection for inventory, machines, buildings, etc.
- Solid steel construction for maximum absorption of impact
- Can be adapted and extended to accommodate any object

Overall length: 80 mm. Overall width: 80 mm. Overall height: 465 mm. Colour: traffic yellow RAL 1023. Material: steel. Type of mounting: with base plate for bolting in place. Weight: 9.2 kg. Base plate length: 160 mm. Base plate width: 140 mm. Panel thickness: 3 mm. Base plate height: 10 mm. Height above ground: 465 mm.

			13
Finish	Place of use		
hot dip galvanised and plastic coated	outdoor use	Ref.	518 757 6G
		€	229.00
plastic coated	indoor use	Ref.	518 755 6G
		€	169.00



Easy installation:

Bolt posts in place, then bolt the rails (C-profile) to the posts using the special mounting technique.

Suitable cover plates can be found under Combinations.

Fastening material available upon request.