



With gas pressure spring and spring loaded pendulum support

More barrier beams
ONLINE!

Barrier beams and access barriers

- With counterbalance weight or gas pressure spring (double stroke) for easy manual operation
- Automatic end position locking when opened or closed when using lock housing
- Height adjustable for optimum adaptation to ground conditions

Barrier beam

Oval aluminium tubing, one-piece, 102 x 82 mm. Non-seizing. Powder coated in pure white RAL 9010. Reflective film on both sides.

Barrier lengths from 5.5 m are fitted with a hoist reinforcement.

Main post and support arm for bolting in place

All steel parts hot dip galvanised or made of stainless steel. Powder coated in traffic red RAL 3020.

Aluminium pendulum support

Spring loaded, silver anodised.

Secured with optional lock case

Barrier with profile cylinder lock, incl. 3 keys. Nesting post with fittings for padlock (not supplied).

Foundation work to be performed by customer.

1 + 2 With counterbalance weight

3 + 4 With gas pressure spring

Accessories

Lock holder with profile cylinder and 3 keys

Automatic end-position lock with stainless steel bolts.

Lock holder with profile cylinder, 3 keys and triangle lock

Fire brigade triangle lock in accordance with DIN 3233, in addition to profile cylinder lock.

1 key incl. automatic end-position locking with stainless steel bolts.

Accessories	Ref.	€
profile cylinder	488 611-2G	339,-
profile cylinder and triangular lock	488 612-2G	459,-

Barrier beam length	m		3	3.5	4	4.5	5	5.5	6	6.5	7	7.5	8
1 with fixed support arm	Ref.		488 587-2G	488 588-2G	488 589-2G	488 590-2G	488 591-2G	488 592-2G	488 594-2G	488 595-2G	488 596-2G	488 597-2G	488 598-2G
	€		1.495,-	1.575,-	1.625,-	1.645,-	1.725,-	1.775,-	1.895,-	1.975,-	2.050,-	2.150,-	2.190,-
2 with spring loaded pendulum support	Ref.		488 599-2G	488 600-2G	488 601-2G	488 602-2G	488 603-2G	488 604-2G	488 605-2G	488 606-2G	488 608-2G	488 609-2G	488 610-2G
	€		1.495,-	1.575,-	1.625,-	1.645,-	1.725,-	1.775,-	1.895,-	1.975,-	2.050,-	2.150,-	2.190,-
3 with fixed support arm	Ref.		488 562-2G	488 563-2G	488 564-2G	488 565-2G	488 566-2G	488 567-2G	488 568-2G	488 570-2G	488 571-2G	488 572-2G	488 573-2G
	€		1.495,-	1.575,-	1.625,-	1.645,-	1.725,-	1.775,-	1.895,-	1.975,-	2.050,-	2.150,-	2.190,-
4 with spring loaded pendulum support	Ref.		488 574-2G	488 575-2G	488 576-2G	488 578-2G	488 579-2G	488 580-2G	488 581-2G	488 582-2G	488 583-2G	488 584-2G	488 586-2G
	€		1.495,-	1.575,-	1.625,-	1.645,-	1.725,-	1.775,-	1.895,-	1.975,-	2.050,-	2.150,-	2.190,-

Electric boom gates

With integrated solar cell

- Optimum blocking of vehicle access points
- High quality solar system incl. rechargeable battery
- No electrical installation necessary
- Convenient operation using the remote control – range approx. 12 m

Housing and barrier beam made of powder coated aluminium with red reflective stripes.

The rechargeable battery (6 V) is charged via the integrated solar system.

Up to 3000 cycles (open/close) with a fully charged battery.

Maintenance free and reliable technology.

Manual operation as well as emergency opening without tools possible.

Technical details

Pedestal stand LxWxH 150 x 150 x 1000 mm, barrier beam Ø 60 mm, weight approx. 18 kg, base plate 200 x 200 x 5 mm.

Included in delivery

Pre-assembled boom gate and one remote control.



WORKSHOP

Barrier beam length	mm	1200	1500	2000	2500
Ref.		707 504-2G	707 505-2G	707 506-2G	707 507-2G
€		1.075,-	1.075,-	1.275,-	1.295,-

Accessories

Additional remote controls

Ref. 114 080-2G € / each 84,90

YELLOW =
7 working days

FREE DELIVERY
SALES FAX: 1 800 677 301 (local rate)

KAISER + KRAFT
EVERYTHING FOR THE BUSINESS.