

1 – 12 | Standard model without floor

- Flexible cabin system made of aluminium profiles and coated wooden panels
- Monoblock units ensure quick and easy assembly
- Scratch resistant, impact resistant and hardwearing – extremely low maintenance

Description: 4-sided, for free standing installation.
Railing height: 1050 mm. Clear height: 2500 mm.
Design of ceiling: mineral fibre acoustic panels inserted in T-profiles. Panel thickness: 53 mm. Section glazing: single glazing. Section width: 1000 mm. Noise insulation: 28 dB(A). Door type: single pane safety glass door. Door clearance width: 885 mm. Door thickness: 40 mm.



Gentian blue RAL
5010



Light grey RAL
7035

Other colours on request.

We will also undertake final assembly at extra cost. Please enquire.



2750 and 3000 mm high sections available on request.

		1	2	3	4	5	6	7	8	9	10	11	12
External length	mm	3100	3100	3100	4100	4100	4100	5100	5100	5100	6100	6100	6100
External width	mm	2100	3100	4100	2100	3100	4100	2100	3100	4100	2100	3100	4100
	Ref.	913 366 6G	913 407 6G	913 446 6G	913 368 6G	913 408 6G	913 447 6G	913 369 6G	913 409 6G	913 449 6G	913 370 6G	913 410 6G	913 450 6G
	€	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request
Accessories													
Standard floor	Ref.	913 377 6G	913 417 6G	913 457 6G	913 378 6G	913 418 6G	913 458 6G	913 379 6G	913 419 6G	913 459 6G	913 380 6G	913 420 6G	913 460 6G
	€	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request
Transport base	Ref.	913 387 6G	913 427 6G	913 467 6G	913 388 6G	913 428 6G	–	913 389 6G	913 429 6G	–	–	–	–
	€	on request	on request	on request	on request	on request	–	on request	on request	–	–	–	–
ISO model	Ref.	913 397 6G	913 437 6G	913 477 6G	913 398 6G	913 438 6G	913 478 6G	913 399 6G	913 439 6G	913 479 6G	913 400 6G	913 440 6G	913 481 6G
	€	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request

13 – 24 | Prefab offices

- Flexible cabin system made of aluminium profiles and coated wooden panels
- Monoblock units ensure quick and easy assembly
- Scratch resistant, impact resistant and hardwearing – extremely low maintenance

Description: 3-sided, for installation on an existing wall. Railing height: 1050 mm. Clear height: 2500 mm.
Design of ceiling: mineral fibre acoustic panels inserted in T-profiles. Panel thickness: 53 mm. Section glazing: single glazing. Section width: 1000 mm. Noise insulation: 28 dB(A). Door type: single pane safety glass door. Door clearance width: 885 mm. Door thickness: 40 mm.



		13	14	15	16	17	18	19	20	21	22	23	24
External length	mm	3100	3100	3100	4100	4100	4100	5100	5100	5100	6100	6100	6100
External width	mm	2100	3100	4100	2100	3100	4100	2100	3100	4100	2100	3100	4100
	Ref.	913 371 6G	913 411 6G	913 451 6G	913 372 6G	913 412 6G	913 452 6G	913 373 6G	913 414 6G	913 453 6G	913 374 6G	913 415 6G	913 454 6G
	€	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request
Accessories													
Standard floor	Ref.	913 381 6G	913 422 6G	913 461 6G	913 382 6G	913 423 6G	913 462 6G	913 384 6G	913 424 6G	913 463 6G	913 385 6G	913 425 6G	913 465 6G
	€	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request
ISO model	Ref.	913 401 6G	913 441 6G	913 482 6G	913 402 6G	913 442 6G	913 483 6G	913 403 6G	913 443 6G	913 484 6G	913 404 6G	913 444 6G	913 485 6G
	€	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request	on request