

Safes

Lightweight model, resistance class I according to EN 1143-1, ECB•S certified



All round multiple panel body.
Multiple panel door, 89 mm thick, with lock bolts on 3 sides.
VdS class I dual bit security lock, with 2 keys.
Fittings protrude 50 mm.
As standard with 2 holes in both the rear panel and base for anchoring.

Full insurance coverage ensured by anchoring in accordance with assembly instructions.
Painted light grey RAL 7035.
Supplied with fastening material.



Security level	Height x width x depth mm	Internal dimensions H x W x D mm	Number of doors pcs.	Number of shelves pcs.	Number of files pcs.	Weight kg	Ref.	€
class I according to EN 1143-1	430 x 420 x 445	350 x 330 x 325	1	1	4	68	113 248-2G	679,-
	780 x 420 x 445	700 x 330 x 325	1	1	8	100	113 249-2G	759,-
	1130 x 570 x 485	1050 x 480 x 365	1	2	12	134	113 250-2G	969,-
	1480 x 570 x 485	1400 x 480 x 365	1	2	21	168	113 251-2G	1.125,-
	1830 x 570 x 485	1750 x 480 x 365	1	3	28	208	113 252-2G	1.245,-
	1300 x 1245 x 485	1220 x 1155 x 365	1	4	35	249	113 253-2G	1.475,-
	1830 x 1245 x 600	1750 x 1155 x 480	2	3	44	278	113 254-2G	1.925,-

Options available at extra cost		Ref.	€
Interior safe, height 200 mm, with cylinder lock		113 257-2G	87,90
Interior safe, height 370 mm, with cylinder lock		113 258-2G	104,90
Pull-out shelf on telescopic rails		113 259-2G	145,-
Pull-out suspension file drawer on telescopic rails		113 260-2G	145,-
[2]	Mechanical combination lock	113 261-2G	179,-
[3]	Electronic lock, 1 master code and 9 user codes	113 262-2G	149,-
[4]	Electronic lock with mechanical emergency access via DB lock (not shown)	123 120-2G	209,-



Steel office cupboards

Security level S1 according to PN-EN 14450 : 2006 or level B according to VDMA 24992 (issued May 1995) and Euro standard S2 according to PN-EN 14450 : 2006



Double panel body on all sides.
Double panel door, 80 mm thick.
Door panel made of 3 mm thick steel.
High quality fire insulation, all-round fireproof seal.
Lock bolts on 4 sides. Multiple nickel plating on the locking bolts, Ø 25 mm.

Dual bit security lock, 2 keys incl.
Lock fittings protrude 50 mm. 2 holes in both the rear panel and base for anchoring.
Painted light grey RAL 7035.



Other colours on request.

Security level	Height x width x depth mm	Internal dimensions H x W x D mm	Number of doors pcs.	Number of shelves pcs.	Number of files pcs.	Weight kg	Ref.	€
S1 according to EN 14450	1250 x 700 x 500	1190 x 628 x 385	1	3	18	125	900 101-2G	789,-
	1500 x 700 x 500	1440 x 628 x 385	1	4	24	145	900 102-2G	899,-
	1950 x 700 x 500	1890 x 628 x 385	1	4	30	180	900 103-2G	1.075,-
	1950 x 950 x 550	1890 x 878 x 435	1	4	50	230	900 104-2G	1.195,-
	1950 x 950 x 550	1890 x 878 x 435	2	4	50	250	900 105-2G	1.325,-
	1950 x 1260 x 550	1890 x 1188 x 435	2	4	65	390	900 106-2G	1.625,-
VDMA B / S2 according to EN 14450	1250 x 700 x 500	1126 x 567 x 343	1	2	21	161	616 082-2G	1.395,-
	1500 x 700 x 500	1376 x 567 x 343	1	3	24	191	616 083-2G	1.645,-
	1950 x 700 x 500	1826 x 567 x 343	1	4	35	241	616 084-2G	1.925,-
	1950 x 950 x 500	1826 x 817 x 343	1	4	50	306	616 085-2G	2.190,-
	1950 x 950 x 500	1826 x 817 x 343	2	4	50	316	616 086-2G	2.250,-
	1950 x 1260 x 500	1826 x 1127 x 343	2	4	75	392	616 088-2G	2.450,-

Options available at extra cost		Ref.	€
Interior safe, height 200 mm, with cylinder lock, for 700 mm external width		900 107-2G	94,90
Interior safe, height 420 mm, with cylinder lock, for external width of 950 or 1260 mm		900 108-2G	139,-
Pull-out suspension file drawer on telescopic rails		969 807-2G	145,-
[2]	Mechanical combination lock	900 098-2G	195,-
[3]	Electronic lock, 1 master code and up to 9 user codes	615 774-2G	165,-
[4]	Electronic lock with mechanical emergency access via DB lock (not shown)	123 120-2G	209,-



OFFICE

YELLOW =
7 working days

FREE DELIVERY
SALES FAX: 1 800 677 301 (local rate)

KAISER + KRAFT
EVERYTHING FOR THE BUSINESS.