
550 Cushion-Ease™




- With holes for excellent drainage and aeration leaving a dry, clean work area.
- General purpose rubber compound.
- This interlocking mat allows on-site customization. Square snap together units of 91x91 cm that can be assembled effortless and laid out from wall to wall or as islands in any direction or shape.
- Compatible with patented MD-Ramp
 System™ for smart safety bevelling solutions.
 Allow out and inside corners.
- Superb anti-fatigue properties due to its unique design underneath and high quality resilient rubber compounds.
- Designed to yield a long service life.
- Resistant to most chemicals and extreme temperatures.
- Free of silicone therefore safe for vehicle painting facilities.









550 Cushion Ease™

	PI	RODUCT SPECIFICATIONS		
Designation	Industrial matting			
Туре	Anti-fatigue Anti-fatigue			
Description	Modular system, open construction			
Material	100% natural rubber compound			
Process	Compression moulding			
Category	Best			
Recommended use	Heavy duty – wet/dry industrial environments			
Colours	Black			
Weight	12 kg/m²			
Thickness	19 mm			
Standard sizes	91 cm x 91 cm			
Custom sizes	N/A			
Special remarks	Accessories: MD Ramp System™ male and female attachable bevels 91 cm, black or yellow. Compatible with Art.Nr. 556 Cushion-Ease Solid. Not for use in contact with animal fats.			
		PRODUCT TESTING		
Tests		Norms	Results	
Compression deflection		U.S.		
	1.4 kg/cm ²	ASTM D575	0.37 cm	
2.8 kg/cm ²		ASTM D575	0.53 cm	
Foam battery		ASTM D3574		
Abrasion resistance		ASTM D3884-01		
	500 Cycles			
	5000 Cycles		2.6% weight loss	
Static coefficient of friction		ASTM C1028-96	0.71	
Elongation		ASTM D412	59.7%	
Breaking load		ASTM D412	33.2 lb	
Graves tear strength		ASTM D 1004	32.1 lb	
Hardness		ASTM D2240-02	68 Shore A	
Anti-slip		DIN 51130 and BG-RULE BGR	DIN 51130 and BG-RULE BGR181	
		FIRE TESTING		
	Critical radiant flux	ASTM E-648		
	Fire retardancy	DIN4102		
		EN 13501-1		
	Flammability test	ASTM D2859	Pass	
ESD		ANSI ESD S7.1 50% Humidity		
Sustainability		 Recyclable material Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals) 		

